

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
 Product name : PRO-FINISH AEROSOL  
 Product code : All except Pro Finish Primers & Silicone Stoppers

#### 1.2. Recommended use and restrictions on use

Recommended use : Finishing, re-finishing and touch-up of wood and laminate furnishings

#### 1.3. Supplier

##### Distributor

Dover Finishing Products, Inc.  
 180 Avenue du Voyageur  
 H9R 6A8 Pointe-Claire, QC - Canada  
 T 514-420-6030  
[dfpservice@dfp.ca](mailto:dfpservice@dfp.ca)

#### 1.4. Emergency telephone number

Emergency number : 1-800-354-4445

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS CA)

Flam. Aerosol 1	H222
Press. Gas (Liq.)	H280
Acute Tox. 4 (Oral)	H302
Acute Tox. 2 (Inhalation:dust,mist)	H330
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Repr. 1B	H360
STOT SE 2	H371
STOT SE 3	H335
STOT SE 3	H336
STOT RE 1	H372
Asp. Tox. 1	H304

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS CA) :

Danger

Hazard statements (GHS-CA) :

H222 - Extremely flammable aerosol.  
 H280 - Contains gas under pressure; may explode if heated.  
 H302 - Harmful if swallowed.  
 H304 - May be fatal if swallowed and enters airways.  
 H315 - Causes skin irritation.  
 H319 - Causes serious eye irritation.  
 H330 - Fatal if inhaled.  
 H335 - May cause respiratory irritation.  
 H336 - May cause drowsiness or dizziness.  
 H360 - May damage fertility or the unborn child.  
 H371 - May cause damage to organs.  
 H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS-CA) :

P201 - Obtain special instructions before use.  
 P202 - Do not handle until all safety precautions have been read and understood.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 - Do not spray on an open flame or other ignition source.  
 P251 - Do not pierce or burn, even after use.  
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.  
 P264 - Wash hands, forearms and face thoroughly after handling.  
 P270 - Do not eat, drink or smoke when using this product

# PRO-FINISH AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P284 - Wear respiratory protection.  
P308+P311 - IF exposed or concerned: Call a POISON CENTER or doctor.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
P330 - Rinse mouth.  
P331 - Do NOT induce vomiting.  
P302+P352 - IF ON SKIN: Wash with plenty of water.  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P310 - Immediately call a POISON CENTER or doctor.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS CA)

30% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
29.75% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%
Acetone	(CAS-No.) 67-64-1	0.025 - 30
n-Butyl acetate	(CAS-No.) 123-86-4	0.03 - 21.25
1-Butanol	(CAS-No.) 71-36-3	6 - 21.25
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	0.06 - 17
Isobutyl alcohol	(CAS-No.) 78-83-1	0.6 - 4.25
Methyl alcohol	(CAS-No.) 67-56-1	0.055 - 4.25
2-Butoxyethanol	(CAS-No.) 111-76-2	0.5 - 2.5
Propylene glycol monomethyl ether	(CAS-No.) 107-98-2	0.5 - 2.5

Comments : The concentrations listed represent actual ranges that result from batch variability.

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.  
First-aid measures after skin contact : IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.  
First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call a POISON CENTER/doctor if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Fatal if inhaled. May cause irritation to the respiratory tract. May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.  
Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.  
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.

# PRO-FINISH AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>), dry chemical powder, foam.

### 5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : None known.

### 5.3. Specific hazards arising from the hazardous product

Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Toxic fumes.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

### 5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Water spray may be ineffective on fire but may protect firefighters and cool closed containers. Use fog nozzles if water is used. Firefighters should wear full protective clothing including self contained breathing apparatus.

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

### 6.2. Methods and materials for containment and cleaning up

For containment : [In case of inadequate ventilation] wear respiratory protection. Eliminate every possible source of ignition. Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not touch spilled material. Do not flush into surface water or sewer system. Wear personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

### 6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Do not breathe gas, fume, Vapour, spray, mist. Do not swallow. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Do not pierce or burn, even after use. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

Additional hazards when processed : Hazardous waste due to potential risk of explosion.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Store away from direct sunlight or other heat sources. Store tightly closed in a dry, cool and well-ventilated place. Store locked up.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

n-Butyl acetate (123-86-4)		
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - ACGIH	Remark (ACGIH)	Eye & URT irr
USA - ACGIH	Regulatory reference	ACGIH 2017

# PRO-FINISH AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Acetone (67-64-1)		
USA - ACGIH	ACGIH TWA (ppm)	250 ppm
USA - ACGIH	ACGIH STEL (ppm)	500 ppm
Isobutyl alcohol (78-83-1)		
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA - ACGIH	ACGIH TWA (ppm)	100 ppm
USA - ACGIH	ACGIH STEL (ppm)	150 ppm
USA - ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
USA - ACGIH	Regulatory reference	ACGIH 2018
Methyl alcohol (67-56-1)		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	250 ppm
Propylene glycol monomethyl ether (107-98-2)		
USA - ACGIH	ACGIH TWA (ppm)	50 ppm
USA - ACGIH	ACGIH STEL (ppm)	100 ppm
USA - ACGIH	Remark (ACGIH)	Eye irr; CNS impair; A4 (Not classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of a lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories)
USA - ACGIH	Regulatory reference	ACGIH 2017
2-Butoxyethanol (111-76-2)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm
USA - ACGIH	Remark (ACGIH)	Eye & URT irr
USA - ACGIH	Regulatory reference	ACGIH 2017
1-Butanol (71-36-3)		
USA - ACGIH	ACGIH TWA (ppm)	20 ppm

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves resistant to chemical penetration

#### Eye protection:

Wear eye/face protection

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Viscous liquid  
Colour : No data available

# PRO-FINISH AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Odour	: Solvent
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: Slower than ether
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 56 - 171 °C
Flash point	: -104 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Relative density	: Heavier than air
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	: No dangerous reactions known under normal conditions of use. Highly reactive with oxidizing agents.
Chemical stability	: Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Incompatible materials. Sparks. Open flame. Direct sunlight. Overheating. Moisture.
Incompatible materials	: oxidizing materials. Reducing agents. Metals. Acids. Alkalis.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. Toxic fumes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Oral: Harmful if swallowed.
Acute toxicity (inhalation)	: Inhalation:dust,mist: Fatal if inhaled.

<b>n-Butyl acetate (123-86-4)</b>	
LD50 oral rat	10768 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 inhalation rat	390 ppm/4h
LC50 inhalation rat (Dust/Mist - mg/l/4h)	0.05 mg/l/4h
LC50 inhalation rat (Vapours - mg/l/4h)	1.86 mg/l/4h
<b>Acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15700 mg/kg
LC50 inhalation rat	50100 mg/m <sup>3</sup> (Exposure time: 8 h)
<b>Isobutyl alcohol (78-83-1)</b>	
LD50 oral rat	2460 mg/kg
LD50 dermal rabbit	3400 mg/kg
LC50 inhalation rat	> 6.5 mg/l/4h
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LD50 dermal	1700 mg/kg
LC50 inhalation rat	29.08 mg/l/4h

# PRO-FINISH AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LC50 inhalation rat (Vapours - mg/l/4h)	27.57 mg/l/4h
<b>Methyl alcohol (67-56-1)</b>	
LD50 oral rat	6200 mg/kg
LD50 dermal rabbit	15840 mg/kg
LC50 inhalation rat	22500 ppm (Exposure time: 8 h)
<b>Propylene glycol monomethyl ether (107-98-2)</b>	
LD50 oral rat	5000 mg/kg
LD50 dermal rabbit	13 g/kg
LC50 inhalation rat	> 7559 ppm (Exposure time: 6 h)
<b>2-Butoxyethanol (111-76-2)</b>	
LD50 oral rat	470 mg/kg
LC50 inhalation rat	486 ppm/4h
<b>1-Butanol (71-36-3)</b>	
LD50 oral rat	700 mg/kg
LD50 oral	2100 mg/kg
LD50 dermal rabbit	3402 mg/kg
LD50 dermal	3400 mg/kg
LC50 inhalation rat	> 8000 ppm/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: May cause damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

<b>PRO-FINISH AEROSOL</b>	
Vaporizer	Aerosol

Symptoms/effects after inhalation	: Fatal if inhaled. May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. May result in aspiration into the lungs, causing chemical pneumonia.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
-------------------	---

<b>n-Butyl acetate (123-86-4)</b>	
LC50 fish 1	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 72h algae (1)	674.7 mg/l (Species: Desmodesmus subspicatus)

<b>Acetone (67-64-1)</b>	
LC50 fish 1	4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
LC50 fish 2	6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Daphnia 2	12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)

<b>Isobutyl alcohol (78-83-1)</b>	
LC50 fish 1	1370 - 1670 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	375 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

# PRO-FINISH AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

<b>Isobutyl alcohol (78-83-1)</b>	
EC50 Daphnia 1	1300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	1070 - 1933 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
<b>Methyl alcohol (67-56-1)</b>	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>Propylene glycol monomethyl ether (107-98-2)</b>	
LC50 fish 1	20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>2-Butoxyethanol (111-76-2)</b>	
LC50 fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>1-Butanol (71-36-3)</b>	
LC50 fish 1	1730 - 1910 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
LC50 fish 2	1740 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	1983 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	1897 - 2072 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h algae (1)	> 500 mg/l (Species: Desmodesmus subspicatus)
EC50 96h algae (1)	> 500 mg/l (Species: Desmodesmus subspicatus)
NOEC chronic crustacea	4.1 mg/l

### 12.2. Persistence and degradability

<b>PRO-FINISH AEROSOL</b>	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

<b>PRO-FINISH AEROSOL</b>	
Bioaccumulative potential	Not established.
<b>n-Butyl acetate (123-86-4)</b>	
Partition coefficient n-octanol/water	1.81 (at 23 °C)
<b>Acetone (67-64-1)</b>	
BCF fish 1	0.69
Partition coefficient n-octanol/water	-0.24
<b>Isobutyl alcohol (78-83-1)</b>	
BCF fish 1	(no bioconcentration expected)
Partition coefficient n-octanol/water	0.79 (at 25 °C)
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
BCF fish 1	0.6 - 15
Partition coefficient n-octanol/water	2.77 - 3.15
<b>Methyl alcohol (67-56-1)</b>	
BCF fish 1	< 10
Partition coefficient n-octanol/water	-0.77
<b>Propylene glycol monomethyl ether (107-98-2)</b>	
BCF fish 1	< 2
Partition coefficient n-octanol/water	-0.437
<b>2-Butoxyethanol (111-76-2)</b>	
Partition coefficient n-octanol/water	0.81 (at 25 °C)
<b>1-Butanol (71-36-3)</b>	
BCF fish 1	0.64
Partition coefficient n-octanol/water	0.785 (at 25 °C)



# PRO-FINISH AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 12.4. Mobility in soil

<b>n-Butyl acetate (123-86-4)</b>	
Partition coefficient n-octanol/water	1.81 (at 23 °C)
<b>Acetone (67-64-1)</b>	
Partition coefficient n-octanol/water	-0.24
<b>Isobutyl alcohol (78-83-1)</b>	
Partition coefficient n-octanol/water	0.79 (at 25 °C)
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
Partition coefficient n-octanol/water	2.77 - 3.15
<b>Methyl alcohol (67-56-1)</b>	
Partition coefficient n-octanol/water	-0.77
<b>Propylene glycol monomethyl ether (107-98-2)</b>	
Partition coefficient n-octanol/water	-0.437
<b>2-Butoxyethanol (111-76-2)</b>	
Partition coefficient n-octanol/water	0.81 (at 25 °C)
<b>1-Butanol (71-36-3)</b>	
Partition coefficient n-octanol/water	0.785 (at 25 °C)

### 12.5. Other adverse effects

Ozone	: Not classified.
Other information	: No other effects known.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Additional information	: Flammable vapours may accumulate in the container. This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimised wherever possible.
Ecology - waste materials	: Hazardous waste due to toxicity.

## SECTION 14: Transport information

### 14.1. Basic shipping description

In accordance with TDG

#### Transportation of Dangerous Goods

UN-No. (TDG)	: UN1950
TDG Primary Hazard Classes	: 2.1 - Class 2.1 - Flammable Gas.
TDG Subsidiary Classes	: 6.1
Transport document description	: UN1950 AEROSOLS, 2.1 (6.1)
Proper Shipping Name (Transportation of Dangerous Goods)	: AEROSOLS

Hazard labels (TDG) :



### 14.2. Transport information/DOT

No additional information available

### 14.3. Air and sea transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. National regulations

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.



# PRO-FINISH AEROSOL

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

### 15.2. International regulations

No additional information available

### SECTION 16: Other information

Date of issue : 11/01/2018  
Revision date : 12/21/2018  
Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



SDS Canada (GHS)\_NEXREG\_NEW

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*