



## Product Data Sheet

### Pro Finish Series (11oz aerosols)

Lines - 7681XX/7682XX/7683XX/7684XX/7686XX

**Overview:** Dover Finishing Products Pro Finish Series of clears, toners, sealers and opaque spray lacquers provides a premium quality pre-catalyzed lacquer system for hobbyists, touch-up professionals and production line applications. Water-clear transparent and high definition toners provide the necessary tools for simple touch-ups to complete refinishing. A high level of compatibility ensure that the Pro Finish line will play well with existing finishes. The look of nitrocellulose with the benefits of pre-cat.

- Pre-catalyzed system
- High solids
- Resistant to yellowing
- Water-clear transparents
- Excellent build
- High definition toners
- Low VOCs vs competitors

### Key properties

21% solid by volume

VOC <550 g/l

Average dry time: 15-20 minutes

Average time to recoat: 30-40 minutes

Average package life: 2 years

### Directions

Clean surface of contaminants using silicone-free solvents such as a cleaning thinner or the DFP Wax-Off. Keep air and surface temperature between 15-25°C. SHAKE WELL BEFORE USING. If you don't hear the mixing ball when shaking, GENTLY tap the base of the can on a hard surface to loosen it. Point spray nozzle at target surface and spray side-to-side moving outwards from about 30-40cm. Work in thin coats to avoid sagging or cracking and wait for each coat to dry before re-coating. Invert can and spray until only propellant comes out to clear the nozzle and tube. See SDS for health and safety measures.