



Full declaration of ingredients

Decking Oil

Binding agents:

- Based on the renewable plant raw materials: sunflower oil, soya oil and thistle oil

Solvents:

- Aliphatic hydrocarbons = dearomatized white spirit (benzene-free)

Pigments:

- Titanium dioxide and iron oxides (yellow, red, brown, black)
- Organic pigments which are in compliance with German Industrial Norm DIN 53160 (fast to perspiration and saliva) and Euro Norm EN 71.3 (safety of children's toys)

Additives:

- Siccatives (are obtained from the respective minerals and are lead-free)
- Ketoximes
- Polysiloxanes (on basis of silicic acid)

The listed ingredients serve to regulate the drying process and to prevent film formation (5 years storage stability) and as a strong water repellent.

According to EC requirements, Osmo Decking Oil does not have to be classified or labelled and will not emit physiologically harmful compounds to environment.

Osmo Decking Oil does not contain biocides and no preservatives.

The dried finish is safe for humans, animals and plants (in compliance with the German Industrial Norm DIN 53160 (resistant to perspiration and saliva) and Euro Norm EN 71.3 (children's toys safety).

Further information, e.g. for the technical characteristics, please refer to the product information.

The above-mentioned information is provided to the best of our knowledge however without any liability.
(Version 09/2020)