SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WEST SYSTEM[®] 405 Filleting Blend

APPLICABLE PRODUCT CODES:405

CHEMICAL FAMILY:Powdered mixture.

INTENDED PRODUCT USES: Thickening agent for liquid epoxy resins.

MANUFACTURER:

Gougeon Brothers, Inc. 100 Patterson Ave. Bay City, MI 48706, U.S.A.

Phone: 866-937-8797 or 989-684-7286

www.westsystem.com

EMERGENCY TELEPHONE NUMBERS (24 HRS):

Transportation

Non-transportation

Poison Hotline: 800-222-1222

2. HAZARDS IDENTIFICATION

Classification of Substance or Mixture

Combustible dust

Label Elements

Hazard Pictogram(s):

None

Signal Word:

WARNING

Hazard Statements:

May form combustible dust concentrations in the air.

Precautionary Statements:

Prevention

Keep away from all ignition sources including heat, sparks and open flame.

Prevent dust accumulations to minimize explosion hazard.

Other Hazards

None known.

3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT NAME	CAS#	CONCENTRATION (%)
Walnut shell flour	NA	60-80
Cellulose pulp	65996-61-4	10-30
Synthetic amorphous pyrogenic silica	112945-52-5	5-10

The exact chemical identity and/or exact percentage (concentration) of each ingredient may be held as confidential business information (CBI). Any ingredient not disclosed in this section may have been determined not to be hazardous to health or the environment, or it may be present at a level below its disclosure threshold.

4. FIRST AID MEASURES

FIRST AID FOR EYESRESPONSE: Flush with water for at least 15 minutes. Remove contact measure if symptoms develop and persist.	SYMPTOMS: Excessive exposure may cause irritation and tearing. tt lenses if present and easy to do. Consult a physician as precautionary
FIRST AID FOR SKIN	SYMPTOMS: May cause skin dryness or slight irritation. RESPONSE: nd persist.
FIRST AID FOR INHALATIONritation or shortness of breath due to temporary lung overload. RESP breathing. Seek medical advice is symptoms persist.	SYMPTOMS: Excessive exposure may cause coughing, respiratory ONSE: Remove to fresh air if symptoms develop and keep comfortable for
FIRST AID FOR INGESTION	SYMPTOMS: No acute adverse health effects expected from amounts

Last Revised: 15JAN19

FIRE FIGHTING MEASURES EXTINGUISHING MEDIA: SUITABLE: Foam, carbon dioxide (CO₂), water, or dry chemical. Fog or mist is recommended if water is used. NON-SUITABLE: Avoid using high pressure media. additional information. Combustion may result in the release of carbon monoxide, carbon dioxide and formaldehyde. protective equipment. Dust may form an explosive mixture in the air, possibly resulting in a secondary explosion. **ACCIDENTAL RELEASE MEASURES** EMERGENCY PROCEDURES: Keep unnecessary and unprotected personnel from entering area. Use appropriate safety and personal protective equipment as indicated in Section 8. MITIGATION AND CLEAN UP PROCEDURES: Eliminate ignition sources. Use methods that avoid generating airborne dust. Use a vacuum with high efficiency particulate air (HEPA) filtration is recommended. Do not create a dust cloud by brushing or sweeping, or using compressed air. HANDLING AND STORAGE STORAGE: Store in cool, dry place. Store in sealed containers to prevent moisture absorption or absorption of other volatile materials. Keep away from sources of ignition. appropriate exhaust ventilation at points of operation where dust can be generated. Avoid using compressed air. Dust may form explosive mixture with air. Take precautionary measures against static discharges. Metal parts of mixing and processing equipment should be earthed/grounded. Dust deposits should not be allowed to accumulate on surfaces. **EXPOSURE CONTROLS/PERSONAL PROTECTION** ENGINEERING CONTROLS: Use with adequate general ventilation and/or local ventilation to keep exposures below established limits. SKIN PROTECTION GUIDELINES: Gloves or a barrier cream may be useful to help prevent skin from drying. RESPIRATORY PROTECTION GUIDELINES: When ventilation cannot be made adequate enough to keep exposures below established limits, use a NIOSH approved respirator with particulate filter, such as a N95 or greater, depending on specific workplace conditions. Consult with your respirator and cartridge supplier to ensure proper selection of respirator and cartridge based on ingredients listed in Section 3 and specific workplace conditions. Use and select a respirator according the guidelines established in OSHA 1910.134 or other applicable respiratory protection standard. ADDITIONAL PROTECTIVE MEASURES: Practice good caution and personal cleanliness to avoid skin and eye contact. Wash thoroughly after handling. Generally speaking, working cleanly and following basic precautionary measures will greatly minimize the exposure to this product under normal use conditions. OCCUPATIONAL EXPOSURE LIMITS: Exposure limits may not be established for this product as a whole. For established exposure limits of specific ingredients in this product, or other available exposure limit information, refer to the table below.

Ingredient Name	CAS#	Exposure Limit Information
Walnut shell flour	NA	Dust and PNOS: ACGIH 10mg/m³, TWA, Inhalable; 3 mg/m³, TWA, Respirable; OSHA PEL 15 mg/m³, TWA, total dust; 5 mg/m³, TWA, Respirable.
Cellulose pulp	65996-61-4	Dust and PNOS: ACGIH 10mg/m³, TWA, Inhalable; 3 mg/m³, TWA, Respirable; OSHA PEL 15 mg/m³, TWA, total dust; 5 mg/m³, TWA, Respirable
Synthetic amorphous pyrogenic silica	112945-52-5	Amorphous silica: OSHA PEL 6 mg/m³ Dust and PNOS: ACGIH 10mg/m³, TWA, Inhalable; 3 mg/m³, TWA, Respirable; OSHA PEL 15 mg/m³, TWA, total dust; 5 mg/m³, TWA, Respirable

9. PHYSICAL AND CHEMICAL PROPERTIES

Page 2 of 5

PHYSICAL FORM:	Powder solid
COLOR:	
ODOR:	
ODOR THRESHOLD:	
pH	
MELTING POINT / FREEZING POINT	
BOILING POINT (760mm/Hg):	
FLASH POINT:	
AUTO IGNITION TEMPERATURE	
LOWER EXPLOSIVE LIMIT (LEL)	
UPPER EXPLOSIVE LIMIT (UEL)	
VAPOR PRESSURE	
SPECIFIC GRAVITY/DENSITY (water = 1)	
BULK DENSITY	
VAPOR DENSITY (air = 1)	
EVAPORATION RATE (Butyl Acetate = 1)	
WATER SOLUBILITY (% BY WT.)	
PARTITION COEFFICIENT, n-OCTANOL/WATER (log Pow)	
KINEMATIC VISCOSITY:	
DECOMPOSITION TEMPERATURE:	
% VOLATILE BY WEIGHT:	
	Dust may form explosive mixtures in air. Explosive properties of this mixture
have not been measured. One or more of the components of this m	ixture have been identified as having the potential to form an explosive mixture
with air when suspended as a dust cloud.	Ŭ I
Kst VALUE:	No data available
MAXIMUM EXPLOSION PRESSURE (Pmax)	No data available
MINIMUM IGNITION ENERGY (MIE):	No data available
MAXIMUM EXPLOSION CONCENTRATION (MEC):	No data available
DUST EXPLOSION CLASSIFICATION:	No data available
. STABILITY AND REACTIVITY	
STABILITY:	Draduat is stable at narmal temporatures and pressures
STADILITY	Product is stable at normal temperatures and pressures.
REACTIVITY/HAZARDOUS REACTIONS:	Product will not react by itself.
INCOMPATIBILITIES:	Strong oxidizing agents.
CONDITIONS TO AVOID:	Avoid settling dust collection and airborne dust formation.
DECOMPOSITION PRODUCTS:	Carbon monoxide, carbon dioxide and possibly formaldehyde at higher
temperatures.	

11. TOXICOLOGICAL AND HAZARD ENDPOINT INFORMATION

Component Name	CAS#	LD ₅₀ Oral	LD ₅₀ Dermal	LC ₅₀ Inhalation
Walnut shell flour	NA	No data	No data	No data
Cellulose pulp	65996-61-4	No data	No data	No data
Synthetic amorphous pyrogenic silica	112945-52-5	>5000 mg/kg	>2000 mg/kg	No data

based on acute toxicity estimation methods using ingredient data.	No specific toxicity data exists for this mixture. Classification is
Oral:	Not classified. Does not meet acute oral toxicity criteria Not classified. Does not meet acute dermal toxicity criteria Not classified. Does not meet acute inhalation toxicity criteria.
SKIN CORROSION / IRRITATION:	Not classified. Does not meet criteria for skin corrosion/irritation.
SERIOUS EYE DAMAGE / IRRITATION:damage/irritation. High dust concentrations may cause mechanical i	
RESPIRATORY SENSITIZATION:	Not classified. Does not meet criteria for respiratory sensitizer.
SKIN SENSITIZATION:	Not classified. Does not meet criteria for skin sensitization.
REPRODUCTIVE TOXICITY:	Not classified. Does not meet criteria for reproductive toxicity.
MUTAGENICITY:	Not classified. Does not meet criteria for mutagenicity.
CARCINOGENICITY:	Not classified. Does not meet criteria for carcinogenicity.

Page 3 of 5

Last Revised: 15JAN19

Synthetic amorphous silica: No evidence of carcinogenicity was observed in multiple animal species following repeated oral or inhalation exposure to synthetic amorphous silica. Similarly, epidemiology studies show no evidence of carcinogenicity in workers who manufacture synthetic amorphous silica.

Treated synthetic amorphous silica: No evidence of cancer in rats exposed for 24 months at 100 mg/kg/d (diet). (ECETOC JACC Report 051 – Synthetic Amorphous Silica, September 2006).

12. ECOLOGICAL INFORMATION

Estimate: Does not meet acute aquatic toxicity criteria.

Estimate: Does not meet chronic aquatic toxicity criteria.

Ingredient	CAS#	Ecotoxicity Classification
		Information
Walnut shell flour	NA	No data available.
Cellulose pulp	65996-61-4	Not classified.
Synthetic amorphous pyrogenic silica	112945-52-5	No data available.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Evaluation of this product using RCRA criteria shows that it is not a hazardous waste, either by listing or characteristics, in its purchased form. It is the responsibility of the user to determine proper disposal methods

Recycle (fuel blending) or reclaim may be preferred methods when conducted in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

US DOT (49 CFR) Non-Bulk

UN NUMBER:	Not applicable Not applicable Not applicable.
CANADA TDG UN NUMBER: SHIPPING NAME: TECHNICAL SHIPPING NAME: HAZARD CLASS:	Not applicable Not applicable.
PACKING GROUP: ICAO/IATA	Not applicable.
UN NUMBER: SHIPPING NAME: TECHNICAL SHIPPING NAME: HAZARD CLASS:	Not applicable Not applicable.
PACKING GROUP: MARINE POLLUTANT:	Not applicable.
IMDG UN NUMBER: SHIPPING NAME: TECHNICAL SHIPPING NAME: HAZARD CLASS: PACKING GROUP:	Not applicable Not applicable Not applicable.

Page 4 of 5

MARINE POLLUTANT Not applicable.

15. REGULATORY INFORMATION

COUNTRY	INVENTORY LIST	STATUS	
United States	TSCA	All ingredients are listed or otherwise compliant.	
Europe	EINECS or ELINCS	All ingredients are listed or otherwise compliant.	
Canada	CEPA (DSL/NDSL)	All ingredients are listed or otherwise compliant.	
Australia	AICS	All ingredients are listed or otherwise compliant.	
Japan	ENCS	No data	
South Korea	KECI	No data	
China	IECSC	No data	
Philippines	PICCS	No data	
New Zealand	NZIoC	No data	

US EPA SARA TITLE III Reporting and Notification Requirements:

STATE REGULATORY INFORMATION:

Chemicals listed below may be specifically regulated by individual states. For details on state regulatory requirements you should contact the appropriate state agency.

COMPONENT NAME

/CAS NUMBER

Synthetic amorphous pyrogenic silica 112945-52-5

STATE CODE

PA, NJ, MA

16. OTHER INFORMATION

REASON FOR ISSUE:	Update to Sections 3, 8, 11 & 15.
PREPARED BY:	Gougeon Brothers, Inc.
SDS CONTACT:	safety@gougeon.com
TITLE:	Health, Safety & Environmental Manager
APPROVAL DATE:	January 15, 2019
SUPERSEDES DATE:	August 16, 2016
SDS VERSION:	

OTHER HAZARD INFORMATION AND RATING SYSTEMS:

HMIS® RATING

HEALTH:	0
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:
0 = Low or None; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

Information in this document is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Gougeon Brothers, Inc. The data on this sheet is related only to the specific material designated herein. Gougeon Brothers, Inc. assumes no legal responsibility for use or reliance upon these data.

Page 5 of 5

Last Revised: 15JAN19