SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

 PRODUCT NAME:
 WEST SYSTEM[®] 423 Graphite Powder

 APPLICABLE PRODUCT CODES:
 423, 423-2, 423-B

 CHEMICAL FAMILY:
 Natural graphite

 INTENDED PRODUCT USES:
 Pigment additive for liquid epoxy resins

 PRODUCT RESTRICTIONS:
 None identified

 SDS VERSION:
 423-2019a

MANUFACTURER:

Gougeon Brothers, Inc. 100 Patterson Ave. Bay City, MI 48706, U.S.A. Phone: 866-937-8797 or 989-684-7286 www.westsystem.com

EMERGENCY TELEPHONE NUMBERS (24 HRS): Transportation

2. HAZARDS IDENTIFICATION

Classification of Substance or Mixture

Carcinogenicity, Category 1A Specific target organ toxicity (repeated exposure - inhalation), Category 1 Combustible dust

Label Elements

Hazard Pictogram(s):



Signal Word: DANGER

Hazard Statements:

H350 May cause cancer H372 Causes damage to organs through prolonged or repeated exposure if inhaled. May form combustible dust concentrations in the air

Precautionary Statements:

 Prevention

 P201 Obtain special instructions before use

 P202 Do not handle until all safety precautions have been read and understood

 P260 Do not breathe dust/fume/mist/vapors/spray

 P264 Wash skin thoroughly after handling

 P270 Do not eat, drink or smoke when using this product.

 P280 Wear protective gloves/eye protection/protective clothing/face protection

 Response

 P308 + P313 If exposed or concerned: Get medical advice/attention

 Storage

 P405 Store locked up

 Disposal

 P501 Dispose of contents and container according to local, state, national and International regulations

Keep away from all ignition sources including heat, sparks and open flame Prevent dust accumulations to minimize explosion hazard

Other Hazards

None known.

3.

COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT NAME	CAS #	CONCENTRATION (%)
Carbon variety graphite (natural graphite)	7782-42-5	60-95
Natural occurring mineral (inert ash)	999999-99-4	10-30
Crystalline silica (variety Quartz, may be in respirable form)	14808-60-7	0.5-5

The exact chemical identity and/or exact percentage (concentration) of each ingredient may be held as confidential business information (CBI). Any ingredient not disclosed in this section may have been determined not to be hazardous to health or the environment, or it may be present at a level below its disclosure threshold.

FIRST AID MEASURES

tearing. RESPONSE: Flush with water for at least 15 minutes. Remove contact lenses if present and easy to do. Consult a physician if symptoms develop and persist.

Wash with mild soap and water. Consult a physician if symptoms develop and persist.

RESPONSE: Remove to fresh air if symptoms develop and keep comfortable for breathing. Seek medical advice if symptoms develop and persist.

ingested under normal conditions of use. RESPONSE: Seek medical attention if a significant amount is ingested.

FIRE FIGHTING MEASURES

media carefully to avoid creating airborne dust. NON-SUITABLE: CO2 or any high-pressure media.

the air. See Section 9 for additional information. Combustion may result in the release of carbon monoxide and carbon dioxide. At temperatures above 1500C, graphite reacts with substances containing oxygen, including water and carbon dioxide. In the case of intensely hot fire events, use sand to cover and isolate graphite.

SPECIAL FIRE FIGHTING PROCEDURES: In the event of a fire, do not breathe fumes. Wear a self-contained breathing apparatus and complete full-body personal protective equipment. Dust may form an explosive mixture in the air, possibly resulting in a secondary explosion.

ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES: Use only non-spark tools and methods. Keep unnecessary and unprotected personnel from entering area. Use appropriate safety and personal protective equipment as indicated in Section 8.

methods that avoid generating airborne dust. Use of a vacuum with high efficiency particulate air (HEPA) filtration is recommended. Do not create a dust cloud by aggressive brushing or sweeping, or using compressed air.

is inert and insoluble and is not expected to pose any soluble ion hazards to the environment. However, good housekeeping practices should be followed and spilled material should be cleaned up and disposed of in an appropriate manner.

HANDLING AND STORAGE

STORAGE TEMPERATURE (min./max.): 0°F (-17°C) / 95°F (35°C)

away from sources of ignition or heat. Avoid storing near oxidizing materials or other incompatible materials identified in Section 10. Store locked up.

HANDLING PRECAUTIONS: Avoid dust formation. Do not breathe dust. Wash hands and face after handling. Provide appropriate exhaust ventilation at points of operation where dust can be generated. Use only equipment that is rated for safe handling of combustible solids. Avoid using compressed air. Dust may form explosive mixture with air. Dust deposits should not be allowed to accumulate on surfaces. Implement routine housekeeping to prevent dust build-up. Natural graphite is a good conductor of electricity. Avoid contact between natural graphite and electrical circuits. Graphite is a highly lubricious material and may present a slip hazard if spilled on smooth walking surfaces.

EXPOSURE CONTROLS/PERSONAL PROTECTION

exposures below established limits.

SKIN PROTECTION GUIDELINES: Liquid-proof gloves (such as neoprene or nitrile) should be used in cases of prolonged or repeated contact to prevent skin irritation or dryness. Barrier creams can be used effectively.

RESPIRATORY PROTECTION GUIDELINES: When ventilation cannot be made adequate enough to keep exposures below established limits, use a NIOSH approved respirator with particulate filter, such as a N95 or greater, depending on specific workplace

conditions. Consult with your respirator and cartridge supplier to ensure proper selection of respirator and cartridge based on ingredients listed in Section 3 and specific workplace conditions. Use and select a respirator according the guidelines established in OSHA 1910.134 or other applicable respiratory protection standard.

Ingredient Name	CAS#	Exposure Limit Information
Carbon variety graphite (natural graphite)	7782-42-5	ACGIH: TLV, 2mg/m ³ , TWA, Respirable; OSHA: 15 mppcf, TWA, Table Z-3 Mineral Dusts NIOSH: TWA, 2.5 mg/ m ³
Naturally occurring mineral (inert ash)	999999-99-4	ACGIH: TLV, 2mg/m ³ , TWA, Respirable;
Crystalline silica (variety Quartz, may be in respirable form)	14808-60-7	ACGIH: TLV, 0.025mg/m ³ , TWA, Respirable OSHA: TWA, 30mg/m ³ / % SiO ₂ + 2, Table Z-3 Mineral Dusts NIOSH: TWA, 0.50mg/ m ³

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM:	Powder solid
COLOR:	
ODOR:	
ODOR THRESHOLD:	
pH.	
MELTING POINT / FREEZING POINT	
BOILING POINT (760mm/Hg):	
FLASH POINT:	No data available
AUTO IGNITION TEMPERATURE	
LOWER EXPLOSIVE LIMIT (LEL)	
UPPER EXPLOSIVE LIMIT (UEL)	No data available
VAPOR PRESSURE	
SPECIFIC GRAVITY/DENSITY (water = 1)	
BULK DENSITY.	
VAPOR DENSITY (air = 1)	
EVAPORATIOIN RATE (Butyl Acetate = 1)	
WATER SOLUBILITY (% BY WT.)	
PARTITION COEFFICIENT, n-OCTANOL/WATER (log Pow)	
KINEMATIC VISCOSITY:	
DECOMPOSITION TEMPERATURE:	
% VOLATILE BY WEIGHT:	
	Dust may form explosive mixtures in air. Explosive properties of this mixture
have not been measured. One or more of the components of this m	ixture have been identified as having the potential to form an explosive mixture
with air when suspended as a dust cloud.	
Kst VALUE:	0-200
MAXIMUM EXPLOSION PRESSURE (Pmax)	
MINIMUM IGNITION ENERGY (MIE):	
MAXIMUM EXPLOSION CONCENTRATION (MEC):	
DUST EXPLOSION CLASSIFICATION:	No data available

10. STABILITY AND REACTIVITY

STABILITY:	Product is stable at normal temperatures and pressures.
REACTIVITY/HAZARDOUS REACTIONS:	Graphite is non-reactive under ambient conditions. No hazardous reaction
INCOMPATIBILITIES:	Oxidizing agents.
CONDITIONS TO AVOID: oxidize above 450°C.	Avoid dust accumulation and airborne dust formation. Graphite will begin to

11. TOXICOLOGICAL AND HAZARD ENDPOINT INFORMATION

Component Name	CAS#	LD ₅₀ Oral	LD ₅₀ Dermal	LC ₅₀ Inhalation
Carbon variety graphite (natural graphite)	7782-42-5	> 2000 mg/kg;	No data	> 2000 mg/m ³ ; OECD
		OECD 423		403
Naturally occurring mineral (inert ash)	999999-99-4	No data available	No data available	No data available

Crystalline silica (variety Quartz, may be in respirable form)	14808-60-7	> 2000 mg/kg; OECD 423	2000 mg/m ³ ; OECD 403
ACUTE TOXICITY:		specific toxicity data exists for t	his mixture. Classification is
based on acute toxicity estimation methods using i		aloggified. Doop not most coult	
Oral: Dermal:			
Inhalation:	Not	classified. Does not meet acute	e inhalation toxicity criteria.
SKIN CORROSION / IRRITATION:	ION : Not classified. Does not meet criteria for skin corrosion or skin		
SERIOUS EYE DAMAGE / IRRITATION:			ia for eye damage or eye
RESPIRATORY SENSITIZATION:	Not	classified. Does not meet criter	ria for respiratory sensitizer.
SKIN SENSITIZATION:			ria for skin sensitization.
REPRODUCTIVE TOXICITY:	Not	classified. Does not meet criter	ria for reproductive toxicity.

Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, in increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue.

SPECIFIC TARGET ORGAN TOXICITY (Single Exposure):......Not classified. Does not meet criteria for STOT SE.

SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure): STOT RE Category 1. May cause damage to organs (lungs) through prolonged or repeated exposure by inhalation.

12. ECOLOGICAL INFORMATION

CHRONIC AQUATIC TOXICITY: No specific test data available for this product. Calculated Estimate: Does not meet chronic aquatic toxicity criteria.

ADDITIONAL ECOTOXICITY INFORMATION: Prevent release to the environment, sewers and natural waters.

Ingredient	CAS#	Ecotoxicity Classification Information
Natural graphite	7782-42-5	Not Classified.
Naturally occurring mineral (inert ash)	999999-99-4	No data available.
Crystalline silica (variety Quartz, may be in respirable form)	14808-60-7	No data available.

13. DISPOSAL CONSIDERATIONS

Reclaim or reuse may be preferred methods when conducted in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

US DOT

UN NUMBER:	Not regulated.
SHIPPING NAME:	Not applicable.
TECHNICAL SHIPPING NAME:	Not applicable.
HAZARD CLASS:	Not applicable.
PACKING GROUP:	Not applicable.
	••

CANADA TDG

UN NUMBER:	Not regulated.
SHIPPING NAME:	
TECHNICAL SHIPPING NAME:	
HAZARD CLASS:	
PACKING GROUP:	

ICAO/IATA

UN NUMBER:	Not regulated.
SHIPPING NAME:	
TECHNICAL SHIPPING NAME:	
HAZARD CLASS:	
PACKING GROUP:	
MARINE POLLUTANT:	

IMDG

UN NUMBER:	Not regulated.
SHIPPING NAME:	
TECHNICAL SHIPPING NAME:	
HAZARD CLASS:	
PACKING GROUP:	
EmS Number:	
MARINE POLLUTANT	

15. REGULATORY INFORMATION

COUNTRY	INVENTORY LIST	STATUS
United States	TSCA	All ingredients are listed or otherwise compliant.
Europe	EINECS or ELINCS	All ingredients are listed or otherwise compliant.
Canada	CEPA (DSL/NDSL)	All ingredients are listed or otherwise compliant. Not listed on NDSL.
Australia	AICS	All ingredients are listed or otherwise compliant.
Japan	ENCS	All ingredients are listed or otherwise compliant.
South Korea	KECL	All ingredients are listed or otherwise compliant.
China	IECSC	All ingredients are listed or otherwise compliant.
Philippines	PICCS	All ingredients are listed or otherwise compliant.
New Zealand	NZLoC	All ingredients are listed or otherwise compliant.

Canada WHMIS Confidential Business Information (CBI): No data available.

US EPA SARA TITLE III Reporting and Notification Requirements:

Subject to Section 302 (TPQ) .	No data available.
Subject to Section 304 (RQ)	No data available.
Subject to Section 313	No data available.

STATE REGULATORY INFORMATION:

Chemicals listed below may be specifically regulated by individual states. For details on state regulatory requirements you should contact the appropriate state agency.

COMPONENT NAME /CAS NUMBER	STATE CODE
Graphite 7782-42-5	MA, PA, NJ
Crystalline silica (quartz) 14808-60-7	MA, PA, NJ, ¹ CA

^{1.} These substances are known to the state of California to cause cancer or reproductive harm, or both.

16. OTHER INFORMATION

REASON FOR ISSUE:	Updates to Sections 3, 8, 11 & 15.
PREPARED BY:	Gougeon Brothers, Inc.

SDS CONTACT:	. safety@gougeon.com
TITLE:	
APPROVAL DATE:	
SUPERSEDES DATE:	
SDS VERSION:	

OTHER HAZARD INFORMATION AND RATING SYSTEMS:

HMIS® RATING

HEALTH:	1
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	



Approximate HMIS and NFPA Risk Ratings Legend: 0 = Low or None; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

Information in this document is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Gougeon Brothers, Inc. The data on this sheet is related only to the specific material designated herein. Gougeon Brothers, Inc. assumes no legal responsibility for use or reliance upon these data.