

WOOD CLEANER AND BRIGHTENER

Wood cleaner and brightener

Biodegradable and safe for vegetation



Wood Cleaner and Brightener is designed to whiten exterior wood that has turned gray and to remove dirt and mold. Wood Cleaner and Brightener is also used to clean a wooden surface before applying a new coat of oil, stain or paint in order to maximize adhesion. Wood Cleaner and Brightener is biodegradable, safe for vegetation and is VOC-free.

Drying Time	12 to 48 hours, depending on temperature and humidity
Available Sizes	3,78 L
Applications	Exterior: Ideal for intensive cleaning and whitening of decks, siding, docks, fences, structures, garden furniture, doors, windows, playground equipment, flower boxes, and other outdoor wood projects.
Surface Types	Raw, oiled or stained wood
Advantages	Low odor Biodegradable
Coverage	200 ft ² /L
Compatibility	Always perform a preliminary test.
Composition	Water, sulfamic acid, oxalic acid, 2-Ethyl hexanol EO-PO surfactant.
COV	0 g/L
Origin	Canada
Tools Cleaning	Water
Disposal of accessories and residues	Wipe off any liquid residue before recycling this container. Consult your municipality for proper disposal of any remaining product.
Storage and Shelf Life	Protect from freezing. If the product has been exposed to cold temperatures, allow it to return to room temperature for 24-48 hours before using. Store in an airtight container at a temperature between 10°C and 25°C. The product has a shelf life of 12 months under these conditions.
Guarantee	Guarantee: Prato-Verde guarantees the quality of its products. They conform to the description provided in the technical data sheets and on the labels suitable for the intended use, in accordance with the instructions written by the company. However, since the manufacturer has no control over the circumstances, methods, and conditions of use, this guarantee only covers the high quality of Prato-Verde products.

Technical Specifications Preparation

1. Protect surrounding vegetation by watering it before and after treatment.
2. The product is ineffective on wet surfaces; ensure the surface to be treated remains dry.
3. Ready to use.
4. Always perform a test of the product on a small area before use.

Technical Specifications Application

1. Apply the product to the dry surface to be treated using a sprayer, floor brush, or paintbrush.
2. Let it sit for 15 minutes.
3. Ensure the surface remains well soaked with the product during the waiting period; reapply as needed.
4. Scrub the surface with a brush and rinse thoroughly with water OR use a high-pressure water jet (1000 to 3000 psi) to remove dirt and grime. Rinse completely until all foam is eliminated.
5. Allow the surface to dry completely and repeat the application if necessary or apply a new coating.

Tips

Protect surrounding vegetation by spraying it with water before and after treatment. The product is ineffective on wet surfaces; ensure that the surface to be treated remains dry. Do not use metal accessories with this product.

WARNINGS

MAY IRRITATE EYES. MAY IRRITATE SKIN. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS.

Do not mix with other household chemicals. Do not breathe fumes. Do not get in eyes. Do not get on skin or clothing. Keep out of reach of children. Close after each use.