




Osmo Application Recommendations

Osmo recommends approx **60g/m²** coverage for highest durability and best stain-resistance.

High wear surfaces include: Floors, stairs, tabletops, countertops and cutting boards.

Different applicators will provide different results in regards to colour and number of coats needed.

Please note: 60g/m² full coverage suggestion is based on woods such as Oak, Walnut, Elm, Cherry and Ash. For very dense wood species such as Maple, the surface will absorb less oil and therefore a lower application amount of 45g/m² is advised.



Scan this QR code to watch our application videos on YouTube!

OSMO CANADA
1-844-OSMOCAN (676-6226)
info@osmo.ca



Easy pads

- Applies 5g / m² per coat
- A minimalistic finish retaining wood texture and providing subtly glazed colours
- Not suitable alone for high-wear surfaces



White, Non-Abrasive Superpad

- Applies 10g / m² per coat
- A minimalistic finish, lower product waste, can be buffed to high lustre
- **Not** recommended for high-wear surfaces



Oil Finish Applicator Fleece

- Applies 15g / m² per coat
- Most user friendly, small build, medium colour intensity
- 3 coats recommended for high-wear surfaces



Flat Brush

- Applies 20g / m² per coat
- Best for textured surfaces, and intensive colour applications
- 2-3 coats recommended for high wear surfaces



Microfibre Roller (4mm nap)

- Applies 30g / m² per coat
- Fastest application, high build for maximum protection
- 2 coats recommended for high-wear surfaces



Spray Finish

- Applies 30g / m² per coat
- **Professional use only** - training recommended
- 2 coats recommended for high-wear surfaces