

# D6

## 6-STAGE TURBINE SYSTEM

PAIR IT WITH YOUR FAVORITE FUJI SPRAY GUN

T-70 (#5070)

T-75G (#5175G)

G-XPC (#9600-G)



*Unmatched Precision. Unbeatable Efficiency. Undiluted.*

Fuji Spray®'s **D6** sets a new benchmark in the spray finishing industry, offering a powerful 6-stage motor rated at 11.5 PSI, engineered for efficient and cooler operation to prolong motor life and maximize return on investment. With 6 pre-set pressure settings, users gain precise control over spray output, ensuring professional-grade results with minimal overspray and waste. Providing consistently warm dry air, the **D6** atomizes even the highest viscosity coatings with virtually no thinning required, achieving stunning finishes and even coverage. The **D6** system is designed and assembled in Canada, built with a rugged design to ensure unmatched longevity whether being used in the workshop or at the job site.

### SPECIFICATIONS

Weight	25.57 lbs.
Dimensions	18 x 15 x 11 in.
Hose Length	30 ft.
Inside Hose Diameter	¾ in.
Hose Connection Type	Turbine - Threaded/Spray Gun - QuickConnect
Filtration	Foam & HEPA (2-Stage)
Voltage	110v or 220v
PSI (Sealed Pressure)	Max 11.5. psi

### KEY FEATURES

- Powerful 6 Stage Motor
- Smart Select Control Panel
- Easy Pause Remote Control (Remote Range - 75 ft.)
- Cool Operation Design
- Advanced 2-Stage Turbo Filtration With Check Filter Light
- Versatile Applications
- Fold Away Spray Gun Holder
- 2 + 1 Year Warranty