

DE-1230-PC Dust Extractor • HEPA Certified to meet EPA RRP Guidelines

Dust Extractor Features

- 3 Layers of dust protection and filtration
- Versatile accessories
 - Work Station
 - Handle
 - Tool case fastening system
- One button Push & Clean flat filter cleaning
- Certified HEPA filter
- Powerful motor with improved air flow

Tech specifications

Voltage mains supply	110 – 120 V ~
Mains frequency	60 Hz
Power input	1200 W
Volume flow air	4500 l/min
Vacuum	250 mbar
Noise level, LpA	60 dBA
Container volume	8 Gal. (30 l)
Dimension W x D x H	15.25" x 22.25" x 22.25"
Weight	32 lbs. (14.5 kg)

Easily accessible flat filter Filter can easily be reached

through an opening in the back.

High volume container

30 liters for applications where a lot of material is extracted.

Large wheels -

Easy maneuverability on uneven surfaces.

High performance motor and turbine

1200 W motor and 1-stage turbine creates 250 mbar pressure and 4500 l/min airflow.



Push & Clean Filter Cleaning

Hose storage

The hose is always ready for use.

AutoStart function

Dust extractor runs only when the power tool is running.

Filtration

3 Layers of Dust Protection and Filtration!



DE-FDBFleece dust bag



DE-FILT Flat filter



DE-HEPA HEPA filter

Hoses

Coaxial Pneumatic



MV-412HA (15') MV-HA33 (33')

1-1/2" x 15' (or 33') with 1-1/4" adapter (MV-412HA-ADAP) Coaxial Electric



MVHA-5 (18') MVHA-10 (33')

1-1/2" x 18' (or 33') with 1-1/4" adapter (MV-412HA-ADAP) General Purpose



MIN6519411 (12') 1-1/2" tapered to 1-1/4" x 12'

HandBlock



91100-A 3/4" x 12' with adapter

Accessories





DE- 1200PBPneumatic control box
Auto ON/OFF



Tool case fastening system

