

Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

### 1 Identification

Product identifier

Trade name: Osmo One Coat Only HS Plus

Other means of identification

Article number: 9203-9271

& mixed shades

Application of the substance

/ the mixture Conjugated Oil Varnish

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Supplier Osmo Wood and Colour Canada Ltd.

420 Thompson Drive - Unit 2 N1T 2K8 Cambridge, ON

Canada

Tel:+1-844-OSMOCAN E-mail: info@osmo.ca

Manufacturer Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Germany

Information department: Product safety department

Tel.: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

Emergency telephone

**number:** 24h-Emergency Phone Number:

For Chemical Emergency, Spill; Leak; Fire Exposure or Accident Call Day or

Night within USA and Canada 1-800-424-9300

Outside USA and Canada 001-703-527-3887 (CCN 16475)

#### 2 Hazard identification

#### Classification of the substance or mixture

Flammable liquids - Category 4 H227 Combustible liquid.

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

Label elements

Hazard pictograms Void Signal word Warning

Hazard statements H227 Combustible liquid.

**Precautionary statements** P102 Keep out of reach of children.

P210 Keep away from heat. No smoking.

P262 Do not get in eyes, on skin, or on clothing.

(Contd. on page 2)



Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

# Trade name: Osmo One Coat Only HS Plus

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with national

regulations.

Information pertaining to particular dangers for man and environment:

Classification system:

NFPA ratings (scale 0 - 4) Health = 0

Fire = 2

Reactivity = 0

HMIS-ratings (scale 0 - 4) Health = 0

Fire = 2 Reactivity = 0

Other hazards CAUTION: Rags, steel wool or waste soaked with this product may

spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent

this.

Always wear a dust mask when sanding.

Observe the general safety regulations when handling chemicals.

## 3 Composition/Information on ingredients

Chemical characterization: Mixtures

**Description:** Mixture of the substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 | 10-30% w/w \*

%

Aspiration hazard – Category 1, H304; Flammable liquids – Category 4,

<del>-</del>Ĭ227

#### 4 First-aid measures

Description of first aid measures

**General information:** Take affected persons out into the fresh air.

After inhalation: Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for

transportation.

After skin contact: Rinse with warm water.

Immediately wash with water and soap and rinse thoroughly. If skin irritation or rash occurs: Get medical advice/attention.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms

persist, consult a doctor.

(Contd. on page 3)

<sup>\*</sup> Actual concentration ranges are withheld as a trade secret.



Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

Trade name: Osmo One Coat Only HS Plus

(Contd. of page 2)

After swallowing: Rinse mouth.

If swallowed, seek medical advice immediately and show this container or

label.

Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed Dizziness

Indication of any immediate

medical attention and special

treatment needed If swallowed or in case of vomiting, danger of entering the lungs.

### 5 Fire-fighting measures

Extinguishing media Suitable extinguishing

agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray

or alcohol resistant foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO) carbon dioxide (CO2)

Advice for firefighters

**Protective equipment:** Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.

General measures for chemical fires.

**Additional information** Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Cool endangered receptacles with water spray.

#### 6 Accidental release measures

Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Wear protective clothing.

For non-emergency

personnel No action shall be taken involving any personal risk or without suitable training.

For emergency responders Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

# Trade name: Osmo One Coat Only HS Plus

(Contd. of page 3)

Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders).

Dispose of the collected material according to regulations.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

**Reference to other sections** See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

Precautions for safe handling Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

General protective and

hygienic measures: Wash hands before breaks and at the end of work.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Information about protection

against explosions and fires: Keep respiratory protective device available.

**Handling:** Even a small sip can lead to life-threatening damage to the lungs. Keep rags

filled with this liquid out of the reach of children.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Information about storage in

one common storage facility: Not required.

Further information about

**storage conditions:** Store receptacle in a well ventilated area.

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 10

**Specific end use(s)** No further relevant information available.

(Contd. on page 5)



Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

Trade name: Osmo One Coat Only HS Plus

(Contd. of page 4)

## 8 Exposure controls/ Personal protection

Control parameters

Components with limit values that require monitoring at the

workplace: The product does not contain any relevant quantities of materials with critical

values that have to be monitored at the workplace.

**Additional information:** The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and

hygienic measures: Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

The usual precautionary measures for handling chemicals should be followed.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

See Section 7 for information on safe handling.

**Breathing equipment:** Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is

independent of circulating air.

Half mask with round thread connection EN 148-1 (screw-on filter) and

combination filter A1 - P2 according to German DIN EN 14387.

Use a properly fitted, air-purifying or air-fed repirator complying with an approved standard if a risk assessment indicates this is necessary.

**Protection of hands:** To avoid skin problems reduce the wearing of gloves to the required minimum.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the

substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates

of diffusion and the degradation

Material of gloves The selection of the suitable gloves does not only depend on the material, but

also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

checked prior to the application.

Penetration time of glove

material The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed.

(Contd. on page 6)



Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

# Trade name: Osmo One Coat Only HS Plus

(Contd. of page 5)

For the permanent contact gloves made of the following

materials are suitable: For the mixture of chemicals mentioned below the penetration time has to be

at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.4 \text{ mm}$ 

For the mixture the penetration time has to be at least 480 minutes

(Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following

materials are suitable:Nitrile rubber, NBREye protection:Tightly sealed gogglesBody protection:Protective work clothing

### 9 Physical and chemical properties

Information on basic physical and chemical properties

**General Information** 

Physical state Liquid

Color: Different according to coloring

Odor: Mild

Odor threshold:Not determined.Melting point/Melting range:Undetermined.Boiling point/Boiling range:> 180 °C (DIN 51751)

Flammability: Not applicable.

**Explosion limits:** 

 Lower:
 0.7 Vol %

 Upper:
 6.0 Vol %

Flash point: > 61 °C (DIN EN ISO 2719)

Auto igniting: 240 °C

**Decomposition temperature:** Not determined.

**pH-value:** Mixture is non-polar/aprotic.

Viscosity:

**Dynamic:** Not determined.

Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water):Not determined.Vapor pressure:3 hPa [20°C]

Vapor pressure:

**Density at 20 °C:** 0.95-1.2 g/cm³ (DIN 51757)

Relative density Not determined.

(Contd. on page 7)



Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

Trade name: Osmo One Coat Only HS Plus

(Contd. of page 6)

Particle characteristics

Not applicable.

Other information

Appearance:

Form: Fluid Important information on protection of health and

environment, and on safety.

Ignition temperature: Product is not selfigniting.

**Danger of explosion:** Product does not present an explosion hazard.

Solvent content:

VOC content: < 350 g/l

Environment Canada VOC Classification: 32 -

Conjugated Oil Varnish

Conjugated oil varnish for sealing wood with a film formation due to the polymerization of naturally occurring conjugated vegetable oil, modified with other natural or synthetic resins of which a minimum of 50% of the resin solids consist of conjugated oils, and that is supplied as

a single component product.

Change in condition

**Evaporation rate** Not determined.

#### 10 Stability and reactivity

**Reactivity** No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided:

Possibility of hazardous

reactions

Conditions to avoid

Reacts with fabric soaked in the product (e.g. cleaning wool).

No decomposition if used and stored according to specifications.

Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

Incompatible materials: Hazardous decomposition

products:

No further relevant information available.

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information: CAUTION: Rags, steel wool or waste soaked with this product may

spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent

this.

(Contd. on page 8)



Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

Trade name: Osmo One Coat Only HS Plus

(Contd. of page 7)

### 11 Toxicological information

Information on toxicological effects Acute toxicity:

	Cui	נט פו	Aicity.	
7	$\overline{D/I}$	CEC	) values	

LD/LC50 values	that are relevant for classification:

CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 / 4h	>5 mg/l (rat)

## CAS: 13463-67-7 titanium dioxide - aerodynamic diameter >10 µm

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

Primary irritant effect:

on the skin: No irritant effect.

Based on available data, the classification criteria are not met.

on the eye: No irritating effect.

Based on available data, the classification criteria are not met.

Sensitization: Sensitizing effect by skin contact is possible with prolonged exposure.

Subacute to chronic toxicity: Based on available data, the classification criteria are not met.

Additional toxicological

information: The product can cause inheritable damage.

#### Carcinogenic categories

IARC (Internation	nal Agency for Research on Cancer)	
CAS: 7631-86-9	silicon dioxide, chemically prepared	3
CAS: 14808-60-7	Quartz (SiO2)	1
CAS: 1333-86-4	Carbon black	2B

### NTP (National Toxicology Program)

CAS: 14808-60-7 Quartz (SiO2) K

### 12 Ecological information

#### **Toxicity**

Aqua		

CAS: 64742-48-9 aliphatic hydrocarbons, C10-C13 n-alkanes, i-alkanes, cyclics, aromatics < 2 %

EC50 / 48h | >1,000 mg/l (Daphnia magna)

IC50 / 72h |>1,000 mg/l (algae) LC50 / 96h |>1,000 mg/l (fish)

(Contd. on page 9)



Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

## Trade name: Osmo One Coat Only HS Plus

(Contd. of page 8)

**Persistence and degradability** No further relevant information available. **Bioaccumulative potential**No further relevant information available. **Mobility in soil**No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

Other adverse effects

Additional ecological information:

General notes: Water hazard class 1 (Self-assesment): slightly hazardous for water

#### 13 Disposal considerations

Waste treatment methods

**Recommendation:** Must not be disposed of together with household garbage. Do not allow

product to reach sewage system.

Disposal must be made according to official regulations.

Uncleaned packagings:

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleansing

agent: Solvent naphtha

Osmo Brush Cleaner and Thinner

### 14 Transport information

**UN-Number** 

DOT/TDG, ADR, ADN, IMDG, IATA Not applicable

UN proper shipping name

DOT/TDG, ADR, ADN, IMDG, IATA Not applicable

Transport hazard class(es)

DOT/TDG, ADR, ADN, IMDG, IATA

**Class** Not applicable

Packing group

DOT/TDG, ADR, IMDG, IATA Not applicable

Environmental hazards:

Marine pollutant: No

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 10)



Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

## Trade name: Osmo One Coat Only HS Plus

(Contd. of page 9)

Special precautions for user Not applicable.

UN "Model Regulation": Not applicable

### 15 Regulatory information

Safety, health and

environmental regulations/ legislation specific for the

substance or mixture

No further relevant information available.

Sara

#### Section 355 (extremely hazardous substances):

None of the ingredients is listed.

#### Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

#### TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

#### Canadian substance listings:

#### Canadian Domestic Substances List (DSL)

All ingredients are listed.

#### Canadian Non-Domestic Substances List (NDSL)

None of the ingredients is listed.

### Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

#### Canadian Ingredient Disclosure list (limit 1%)

CAS: 7631-86-9 silicon dioxide, chemically prepared

GHS label elements The product is classified and labeled according to the Globally Harmonized

System (GHS).

Hazard pictograms Void Signal word Warning

Hazard statements H227 Combustible liquid.

**Precautionary statements** P102 Keep out of reach of children.

P210 Keep away from heat. No smoking.

P262 Do not get in eyes, on skin, or on clothing.
P271 Use only outdoors or in a well-ventilated area.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with national

regulations.

(Contd. on page 11)



Date of issue 11/14/2025 Version number 19.0 Revision: 11/14/2025

Trade name: Osmo One Coat Only HS Plus

(Contd. of page 10)

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

**Department issuing SDS:** product safety department

Contact:Hr. Dr. StarpDate of previous version05/19/2020Date of preparation11/14/2025

Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

**Sources** ESIS: European chemical Substances Information System

ECHA Portal

Safety data sheets from raw material suppliers

\* Data compared to the

previous version altered. Additions, deletions, revisions

CA