

PRODUCT DESCRIPTION:

Smart Strip® Advanced Paint Remover strips multiple layers of acrylic, latex, oil, and water-based paints, varnishes, stains, and coatings. Effective on most woods, metals, and masonry surfaces. Usually requires only one application. This water-based formula works effectively indoors and out, is do-it-yourself friendly, and completely non-caustic.

This product features non-aerosol, **Bag-on-Valve (BoV)** technology ensuring maximum product use without flammable aerosol combustion.

MAIN FEATURES & BENEFITS:

- Removes multiple layers of acrylic, latex, oil, and water-based paints, varnishes, and stains.
- Do it Yourself / User Friendly; Easy to Use
- Usually works in a single application! Dwell Time: 1 – 18 hours depending on coating present
- Does **NOT** contain Methylene Chloride, NMP, or caustic chemicals.
- Compatible with most surface types. See full list under “Recommended Substrates”.
- Water-based gel formula clings to vertical surfaces.
- Suitable for interior and exterior applications.
- **Smart Strip Advanced** is pH neutral and non-flammable.

TECHNICAL DATA:

Appearance:	Liquid in a bag-on-valve aerosol can
Color:	White
Odor:	Aromatic
Coverage:	6 - 8 ft ² /can, 0.56 - 0.74 m ² /can
Shelf Life:	Approx. 3 years when stored in a tightly sealed container at room temperature, in a clean, dry environment. Exact shelf life may vary.



RECOMMENDED SUBSTRATES:

Smart Strip Advanced may be used on brick, cast iron, cement, concrete, copper, enamel, granite, iron, marble, plaster, steel, slate, stone, terra cotta, terrazzo, tin, and wood. It is not recommended for use on some types of glass, plexiglass, some plastics, vinyl, drywall, or rubber. If you do not see your substrate in this section, or are unsure of compatibility, perform a small test to determine product efficiency.

Smart Strip Advanced works on most oil, acrylic, latex, and water-based paints, stains, and varnishes. Will not typically remove epoxy, alkyd, lead, elastomeric, or urethane coatings. Ultimately, coating chemistry determines compatibility. **ALWAYS perform a test before full application, to ensure product effectiveness.**

PRODUCT TESTING:

Testing is highly recommended before full use of this product to ensure product effectiveness, application thickness, and proper dwell time for your specific project. Failure to do a test patch may result in failed applications, unnecessary additional applications, or application of the wrong product.

SURFACE & AIR TEMPERATURES:

Smart Strip Advanced is less effective in colder temperatures. Not recommended below 40 °F / 4.4 °C. For best results, use in temperatures between 40 °F and 90 °F / 4.4 °C and 32.2 °C. Product effectiveness is increased in warmer temperatures, but will dry out more quickly. Do not allow product to dry before removal is complete.

PREPARATION:

Make sure the surface is clean, dry, and free from any loose debris.

APPLICATION & SPREAD RATE:

Wear personal protective equipment to cover your eyes and skin.

Spray **Smart Strip Advanced** in an even layer directly onto the painted surface. Cover with the **Performance Paper™** included under the cap and smooth gently. The **Performance Paper™** logo and directions should be facing you during application. Wipe the actuator tip clean after application, or before subsequent uses.

DWELL TIME:

The time required for softening/lifting of coatings will vary according to the number of layers present, the type of coatings being removed, and the surface temperature. Pre-project testing will help determine the proper work time. Higher temperatures will speed up the removal process, but the product may dry out more quickly.

Allow **1 - 18** hours to remove paint layers. Check the remover periodically to ensure **Smart Strip Advanced** hasn't dried out or hardened. If this occurs, the paint remover will stop removing the coating beneath. Reapply another thin coat to hardened areas to reactivate the gel.

REMOVAL:

A NOTE ABOUT REMOVING STAINS & VARNISHES FROM WOOD: Agitation at the conclusion of the removal process is necessary to completely remove the stain or varnish from the wood substrate.

Remove **Smart Strip Advanced** with water using a low pressure wash or water and sponge, completely cleaning the surface of product and residue. Surface may require some agitation with a nylon bristled brush. Dispose of waste in accordance with local regulations.

AVAILABILITY & COST:

Smart Strip® Advanced Paint Remover is available in 14oz Bag on Valve cans. **Dumond®** products are available through a nationwide network of paint and hardware stores, safety supply distributors, or online. For an in-person outlet nearest you, please visit www.dumondglobal.com. Once on the website, type your postal/zip code into the dealer locator to find addresses and phone numbers of your nearest dealers.

HEALTH & SAFETY REQUIREMENTS:

The full Safety Data Sheet (SDS) for **Smart Strip® Advanced Paint Remover** can be found online at www.dumondglobal.com. View the SDS **BEFORE** product use for required safety information.

CAUTION: CAUSES SERIOUS EYE IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

CONTAINS: Benzyl Alcohol, Calcined Kaolin

Avoid contact with skin, eyes or clothing. Do not breathe vapor or spray mist. Use Outdoors or in a well-ventilated indoor area. Wear personal protective equipment and remove after handling this product. Wash thoroughly after handling it before eating, drinking, smoking, or using toilet facilities. Follow all precautions even after container is emptied.

FIRST AID: Consult a Physician immediately if any of the following symptoms persist or you feel unwell.

EYE CONTACT: Rinse cautiously with plenty of water, also under the eyelids, for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

SKIN CONTACT: Wash thoroughly with soap and water until no traces of the chemical remain. Remove contaminated clothing and shoes. If skin irritation or rash occurs, seek medical attention.

INHALATION: Remove exposed individual(s) to fresh air and keep comfortable for breathing for 20 minutes.

INGESTION: Rinse mouth. If conscious, give 2 glasses of water to dilute. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

For additional emergency assistance, please call **1-800-535-5053** in the United States.

International assistance is available at **1-325-323-3500**. Both numbers are available **24/7/365**.

STORAGE: Store tightly closed in a cool, dry, well-ventilated place. Do not expose the can to heat or store at temperatures above 120°F (49°C). Do not freeze.

KEEP OUT OF THE REACH OF CHILDREN

WARRANTY:

Dumond, LLC. warrants all its products to be free from defects and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PURPOSE. **Dumond, LLC.'s** liability shall be limited in all events to supplying sufficient products to re-treat the specific areas to which defective product(s) have been applied. **Dumond, LLC.** shall have no other liability, including liability for incidental, consequential, or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of **Dumond, LLC.** or its distributors and dealers.



Technical Services:

Dumond, LLC's expert staff is available to answer technical questions and provide product-specific information. For business hours, see our website for more information.

Address: 253 S. Bailey Road
Downingtown, PA 19335
Phone: (610)383-6061
Email: info@dumondglobal.com
Website: www.dumondglobal.com