

TECHNICAL DATA SHEET**Identification of the product and of the company/undertaking****Product identifier**


9191231801	Masking Tape 120° Lime Line, 18mm x 50m
9191232401	Masking Tape 120° Lime Line, 24mm x 50m
9191233001	Masking Tape 120° Lime Line, 30mm x 50m
9191233601	Masking Tape 120° Lime Line, 36mm x 50m
9191234801	Masking Tape 120° Lime Line, 48mm x 50m

Details of the supplier:

Company: Mirka Ltd
Address: Pensalavägen 210
FI-66850 Jeppo, Finland
Phone: +358 20 760 2111
National contact: sales@mirka.com

Description

Highest grade automotive masking tape recommended for wet sanding applications. Suitable for aircraft painting. Saturated semi crepe paper masking tape coated with specially developed cross-linked solvent based natural rubber adhesive.



Applications

- Wet sanding water proof.
- Guaranteed spray painting oven use in 120°C for 30 minutes.
- Aircraft painting

Properties

- Wet sanding.
- 120°C oven use for 30 minutes
- Suitable for both metallic and plastic surfaces
- Absolute residue free removal
- Various surface options to cover special requirements
- Excellent tape to tape adhesion
- Solvent and thinner resistant
- Easy tear
- Excellent conformability
- Suitable for water and solvent based paints
- Easy curving
- Easy application on uneven surfaces

Nominal values

Backing

Impregnated Crepe Paper

Adhesive

Solvent-based, Natural Rubber

Tensile Strength MD

110 ± 30 (N/25mm) | ~ 25 (lb/in)
TM 5004 by Afera

Elongation at Break MD

10 ± 3 (%)
TM 5004 by Afera

Peel Adhesion on Stainless Steel

5 ± 1 (N/25mm) | ~ 18 (oz/in)
TM 5001 by Afera

Paper thickness

110 ± 15 (µm) | ~ 4,33 (mils)

Total thickness

135 ± 25 (µm) | ~ 5,31 (mils)

Application Range

120°C for 30 minutes

