

SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	W 9F 9G GC @ 9BH 65 G98 K D-B; GH5 -BG! BCB F9; I @ H98
Other means of identification	All W SERIES STAIN COLOURS W 9F 9G GC @ 9BH 65 G98 K D-B; GH5 -BG! BCB F9; I @ H98
Recommended use	Fast Dry Pigmented Wiping Stains
Recommended restrictions	None known.
Manufacturer information	John E. Goudey Manufacturing Limited 21 Primrose Avenue Toronto, ON M6H 3V1 CA Phone: (416)531-4669
Supplier	See above.

2. Hazards Identification

Physical hazards	Flammable liquids	Category 4
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1 (central nervous system)
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	

Label elements



Signal word

Danger

Hazard statement

Combustible liquid.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Causes damage to organs (central nervous system) through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

Precautionary statement

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mist or vapor. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product.

Response	In case of fire: Use appropriate media to extinguish. IF ON SKIN: Wash with plenty of water. Specific treatment (see information on this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Benzene, ethyl-		100-41-4	1-5*
Carbon black		1333-86-4	0.1-1*
Ferric oxide		1309-37-1	1-5*
Heavy aromatic solvent naphtha (petroleum)		64742-94-5	45-70*
Hydrous magnesium silicate		14807-96-6	0.1-1*
Naphtha (petroleum), heavy alkylate		64741-65-7	0.1-1*
Silica, amorphous, fumed, crystalline free		112945-52-5	0.1-1*
Solvent naphtha (petroleum), medium aliphatic		64742-88-7	1-5*
Stoddard solvent		8052-41-3	0.1-1*
Xylene		1330-20-7	10-30*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments	*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret. US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.
-----------------------------	--

4. First Aid Measures

Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	IF ON SKIN: Wash with plenty of water. Specific treatment (see information on this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Treat patient symptomatically.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

Hazardous combustion products May include and are not limited to: Oxides of carbon.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Never return spills to original containers for re-use. Clean surface thoroughly to remove residual contamination. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

Environmental precautions Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear appropriate personal protective equipment. Do not breathe mist or vapor. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Avoid prolonged exposure. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	STEL	543 mg/m3	
		125 ppm	
	TWA	434 mg/m3 100 ppm	
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable particles.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	TWA	1590 mg/m3	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Stoddard solvent (CAS 8052-41-3)	TWA	400 ppm	
		572 mg/m ³	
Xylene (CAS 1330-20-7)	STEL	100 ppm	
		651 mg/m ³	
	TWA	150 ppm	
		434 mg/m ³	
		100 ppm	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m ³	Inhalable
Ferric oxide (CAS 1309-37-1)	STEL	10 mg/m ³	Fume.
	TWA	5 mg/m ³	Fume.
		5 mg/m ³	Dust.
		3 mg/m ³	Respirable fraction.
		10 mg/m ³	Total dust.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	TWA	200 mg/m ³	Non-aerosol.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	200 mg/m ³	Non-aerosol.
Stoddard solvent (CAS 8052-41-3)	STEL	580 mg/m ³	
Xylene (CAS 1330-20-7)	TWA	290 mg/m ³	
	STEL	150 ppm	
	TWA	100 ppm	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m ³	Inhalable fraction.
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m ³	Respirable fraction.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	TWA	200 mg/m ³	Non-aerosol.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable fraction.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	200 mg/m ³	Non-aerosol.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 fibers/ml	
		2 mg/m3	Respirable fraction.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	TWA	525 mg/m3	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	STEL	543 mg/m3	
		125 ppm	
	TWA	434 mg/m3 100 ppm	
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.
		10 mg/m3	Total dust.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	TWA	1590 mg/m3	
		400 ppm	
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	3 mg/m3	Respirable dust.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	TWA	1590 mg/m3	
		400 ppm	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	1590 mg/m3	
		400 ppm	
Stoddard solvent (CAS 8052-41-3)	TWA	525 mg/m3	
		100 ppm	
Xylene (CAS 1330-20-7)	STEL	651 mg/m3 150 ppm	
		TWA	434 mg/m3 100 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Ferric oxide (CAS 1309-37-1)	PEL	10 mg/m3	Fume.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	PEL	400 mg/m3	
		100 ppm	
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	PEL	400 mg/m3	
		100 ppm	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	PEL	400 mg/m3	
		100 ppm	
Stoddard solvent (CAS 8052-41-3)	PEL	2900 mg/m3	
		500 ppm	
Xylene (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
		0.8 mg/m3	
Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)	TWA	0.8 mg/m3	
		20 mppcf	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	TWA	20 ppm	
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	TWA	200 mg/m3	Non-aerosol.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.
Stoddard solvent (CAS 8052-41-3)	TWA	100 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Benzene, ethyl- (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
		435 mg/m3	
Carbon black (CAS 1333-86-4)	TWA	100 ppm	
		0.1 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Ferric oxide (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.
Hydrous magnesium silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	TWA	400 mg/m3 100 ppm	
Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)	TWA	6 mg/m3	
Stoddard solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
Xylene (CAS 1330-20-7)	STEL	655 mg/m3 150 ppm	
	TWA	435 mg/m3 100 ppm	

Biological limit values

ACGIH Biological Exposure Indices		Determinant	Specimen	Sampling Time
Components	Value			
Benzene, ethyl- (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

Canada - Alberta OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	Can be absorbed through the skin.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	Can be absorbed through the skin.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	Can be absorbed through the skin.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	Can be absorbed through the skin.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	Can be absorbed through the skin.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	Can be absorbed through the skin.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	Can be absorbed through the skin.

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Impervious gloves. Confirm with reputable supplier first.
Other	As required by employer code.
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance	Liquid
Physical state	Liquid.
Form	Liquid.
Color	Colored
Odor	Aromatic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	< 32 °F (< 0 °C)
Initial boiling point and boiling range	181.4 - 354.2 °F (83 - 179 °C)
Pour point	Not available.
Specific gravity	0.95 - 1.05
Partition coefficient (n-octanol/water)	Not available.
Flash point	149.0 °F (65.0 °C) TCC
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	5.5 mm Hg @20C
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Negligible
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	16 seconds on a Zahn # 2
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC (Weight %)	716 - 788 g/l

10. Stability and Reactivity

Reactivity	This product may react with strong oxidizing agents.
-------------------	--

Possibility of hazardous reactions	Hazardous polymerization does not occur.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Do not mix with other chemicals.
Incompatible materials	Strong acids. Strong oxidizing agents. Halogens. Aluminum. Strong bases.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause stomach distress, nausea or vomiting.
Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.

Components	Species	Test Results
Benzene, ethyl- (CAS 100-41-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	17800 mg/kg, HSDB 15380 mg/kg, CCOHS: Cheminfo 17.8 ml/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Mouse	> 8000 ppm, 20 Minutes, ECHA
	Rat	4000 ppm, 4 Hours, CCOHS: Cheminfo
<i>Oral</i>		
LD50	Rat	5460 mg/kg, HSDB 3500 mg/kg, Sigma Aldrich 5.5 g/kg, ECHA/HSDB
Carbon black (CAS 1333-86-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 3000 mg/kg
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Rat	> 15400 mg/kg > 10000 mg/kg, ECHA > 8000 mg/kg, ECHA/HSDB
Ferric oxide (CAS 1309-37-1)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Not available	

Components	Species	Test Results
<i>Oral</i> LD50	Rat	> 10000 mg/kg, ECHA > 5000 mg/kg, ECHA
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)		
Acute <i>Dermal</i> LD50	Rabbit	> 6000 mg/kg, 24 Hours > 4000 mg/kg, 24 Hours > 2000 mg/kg, 24 Hours, ECHA
	Rat	> 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i> LC50	Rat	> 7.5 mg/L, 6 Hours, ECHA > 4.3 mg/L, 4 Hours, ECHA > 0.1 mg/L, 8 Hours, ECHA
<i>Oral</i> LD50	Rat	> 5000 mg/kg > 2000 mg/kg, ECHA 7050 mg/kg, HMIRC 5800 mg/kg, ECHA 4820 mg/kg, ECHA
Hydrous magnesium silicate (CAS 14807-96-6)		
Acute <i>Dermal</i> LD50	Rat	> 2000 mg/kg, ECHA
<i>Inhalation</i> LC50	Rat	> 2.1 mg/L, 4 h, ECHA
<i>Oral</i> LD50	Rat	> 5000 mg/kg, ECHA
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)		
Acute <i>Dermal</i> LD50	Rabbit	> 6000 mg/kg, 24 Hours, ECHA > 3750 mg/kg, 24 Hours, ECHA > 3000 mg/kg, 24 Hours, ECHA > 2000 mg/kg, ECHA > 2000 mg/kg, 24 Hours, ECHA > 1900 mg/kg, 24 Hours, ECHA
<i>Inhalation</i> LC50	Rat	> 8530 mg/m3, 4 Hours, ECHA > 7970 mg/m3, 4 Hours, ECHA > 7630 mg/m3, 4 Hours, ECHA > 7300 mg/m3, 4 Hours, ECHA > 5830 mg/m3, 4 Hours, ECHA > 5740 mg/m3, 4 Hours, ECHA > 5610 mg/m3, 4 Hours, ECHA > 5470 mg/m3, 4 Hours, ECHA > 5300 mg/m3, 4 Hours, ECHA > 5280 mg/m3, 4 Hours, ECHA > 5260 mg/m3, 4 Hours, ECHA

Components**Species****Test Results**

> 5250 mg/m3, 4 Hours, ECHA
 > 5240 mg/m3, 4 Hours, ECHA
 > 5220 mg/m3, 4 Hours, ECHA
 > 5200 mg/m3, 4 Hours, ECHA
 > 5170 mg/m3, 4 Hours, ECHA
 > 5160 mg/m3, 4 Hours, ECHA
 > 5100 mg/m3, 4 Hours, ECHA
 > 5080 mg/m3, 4 Hours, ECHA
 > 5050 mg/m3, 4 Hours, ECHA
 > 5040 mg/m3, 4 Hours, ECHA
 > 5020 mg/m3, 4 Hours, ECHA
 > 5000 mg/m3, 4 Hours, ECHA
 > 4980 mg/m3, 4 Hours, ECHA
 > 4970 mg/m3, 4 Hours, ECHA
 > 4420 mg/m3, 4 Hours, ECHA
 > 5.4 mg/L, 4 Hours, ECHA
 > 5.1 mg/L, 4 Hours, ECHA
 > 5.1 mg/L, 4 Hours, ECHA
 > 5 mg/L, 4 Hours, ECHA
 > 5 mg/L, 4 Hours, ECHA
 73680 mg/L, 4 Hours, HSDB
 >= 5060 mg/m3, 4 Hours, ECHA
 61 mg/L, 4 Hours, HSDB

Oral
 LD50

Rat

> 7000 mg/kg, ECHA
 > 6000 mg/kg, ECHA
 > 5570 mg/kg, ECHA
 > 5200 mg/kg, ECHA
 > 5000 mg/kg, ECHA
 > 4800 mg/kg, ECHA
 > 4500 mg/kg, ECHA
 > 25 ml/kg, HSDB
 14063 mg/kg, ECHA
 6620 mg/kg, ECHA
 5800 mg/kg, ECHA
 5390 mg/kg, ECHA
 4820 mg/kg, ECHA

Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)

Acute

Dermal

LD50

Rabbit

> 5000 mg/kg, 24 Hours, ECHA
 > 2000 mg/kg, 24 Hours

Inhalation

LC50

Rat

> 58.8 mg/L, 4 Hours, ECHA
 > 2.1 mg/L, 4 Hours, ECHA
 > 0.7 mg/L, 4 Hours, ECHA
 > 0.1 mg/L, 4 Hours, ECHA

Components	Species	Test Results
<i>Oral</i> LD50	Mouse	> 15000 mg/kg, HSDB
	Rat	> 3160 mg/kg > 10000 mg/kg, ECHA > 5000 mg/kg, ECHA > 3300 mg/kg 3160 mg/kg, LOLI
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)		
Acute <i>Dermal</i> LD50	Rabbit	> 4000 mg/kg, 24 Hours > 2000 mg/kg > 2000 mg/kg, 24 Hours 3000 mg/kg, NIOSH
<i>Inhalation</i> LC50	Cat	> 6.4 mg/L, 6 Hours
	Rat	> 7.5 mg/L, 6 Hours > 6 mg/L, 4 Hours, ECHA > 5.7 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA > 4.6 mg/L, 4 Hours, ECHA > 4.5 mg/L, 4 Hours, ECHA > 4.3 mg/L, 4 Hours > 0.1 mg/L, 8 Hours 5.3 mg/l/4h, NIOSH
<i>Oral</i> LD50	Rat	> 20000 mg/kg > 5000 mg/kg, NIOSH > 25 ml/kg
Stoddard solvent (CAS 8052-41-3)		
Acute <i>Dermal</i> LD50	Rabbit	> 3000 mg/kg
<i>Inhalation</i> LC50	Rat	> 5500 mg/m3
<i>Oral</i> LD50	Rat	> 5000 mg/kg
Xylene (CAS 1330-20-7)		
Acute <i>Dermal</i> LD50	Rabbit	> 5000 ml/kg, 4 Hours, ECHA > 43 g/kg, HSDB 12126 mg/kg, 24 Hours, ECHA
<i>Inhalation</i> LC50	Mouse	3907 mg/L, 6 Hours, HSDB 3907 ppm, 6 Hours, HSDB
	Rat	6700 ppm, 4 Hours, ECHA

Components	Species	Test Results
		6580 ppm, 4 Hours, ECHA
		6350 ppm, 4 Hours, ECHA/HSDB
		6247 ppm, 4 Hours, ECHA
		5922 ppm, 4 Hours, ECHA
Oral LD50	Mouse	5627 mg/kg, ECHA/HSDB
		5251 mg/kg, ECHA
	Rat	> 4000 mg/kg, ECHA
		6670 mg/kg, HSDB
		4300 mg/kg, ECHA/HSDB
		3523 mg/kg
		10 ml/kg, ECHA
Skin corrosion/irritation	Causes skin irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer. See below.	
ACGIH Carcinogens		
Benzene, ethyl- (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Carbon black (CAS 1333-86-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Crystalline silica (CAS 14808-60-7)	A2 Suspected human carcinogen.	
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Canada - Alberta OELs: Carcinogen category		
Crystalline silica (CAS 14808-60-7)	Suspected human carcinogen.	
Canada - Manitoba OELs: carcinogenicity		
CARBON BLACK, INHALABLE FRACTION (CAS 1333-86-4)	Confirmed animal carcinogen with unknown relevance to humans.	
ETHYL BENZENE (CAS 100-41-4)	Confirmed animal carcinogen with unknown relevance to humans.	
KEROSENE (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR (CAS 64742-88-7)	Confirmed animal carcinogen with unknown relevance to humans.	
KEROSENE (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR (CAS 64742-94-5)	Confirmed animal carcinogen with unknown relevance to humans.	
SILICA, CRYSTALLINE-ALPHA.-QUARTZ, RESPIRABLE FRACTION (CAS 14808-60-7)	Suspected human carcinogen.	
Canada - Quebec OELs: Carcinogen category		
Crystalline silica (CAS 14808-60-7)	Suspected carcinogenic effect in humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Benzene, ethyl- (CAS 100-41-4)	Volume 77 - 2B Possibly carcinogenic to humans.	
Carbon black (CAS 1333-86-4)	Volume 65, Volume 93 - 2B Possibly carcinogenic to humans.	
Crystalline silica (CAS 14808-60-7)	Volume 68, Volume 100C 1 Carcinogenic to humans.	

Ferric oxide (CAS 1309-37-1)	Volume 1, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.
Hydrous magnesium silicate (CAS 14807-96-6)	Volume 42, Supplement 7, Volume 93 - 3 Not classifiable as to carcinogenicity to humans. Volume 93 - 2B Possibly carcinogenic to humans.
Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)	Volume 68 - 3 Not classifiable as to carcinogenicity to humans.
Stoddard solvent (CAS 8052-41-3)	Volume 47 - 3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

- Benzene, ethyl- (CAS 100-41-4)
- Carbon black (CAS 1333-86-4)
- Crystalline silica (CAS 14808-60-7)

US NTP Report on Carcinogens: Known carcinogen

Crystalline silica (CAS 14808-60-7) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Crystalline silica (CAS 14808-60-7) Cancer

Reproductive toxicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.
Teratogenicity	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Xylene is considered fetotoxic in humans, based on observations of reduced fetal weight, delayed ossification and persistent behavioural effects in animal studies in the absence of maternal toxicity.
Specific target organ toxicity - single exposure	May cause respiratory irritation. May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Causes damage to organs (central nervous system) through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. Significant lung effects have been observed in animals following exposure to airborne concentrations of Carbon Black of less than 100 mg/m3.

12. Ecological Information

Ecotoxicity See below

Ecotoxicological data

Components	Species	Test Results
Benzene, ethyl- (CAS 100-41-4)		
Algae	IC50	Algae 4.6 mg/L, 72 Hours
Crustacea	EC50	Daphnia 2.1 mg/L, 48 Hours
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 1.37 - 4.4 mg/L, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 7.5 - 11 mg/L, 96 hours
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)		
Algae	IC50	Algae 2.5 mg/L, 72 Hours
Crustacea	EC50	Daphnia 0.95 mg/L, 48 Hours
Aquatic		
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss) 8.8 mg/L, 96 hours
		8.8 mg/L, 96 hours
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)		
Algae	IC50	Algae 30000 mg/L, 72 Hours
Aquatic		
Crustacea	EC50	Water flea (Daphnia pulex) 2.7 - 5.1 mg/L, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss) 8.8 mg/L, 96 hours
		8.8 mg/L, 96 hours

Components	Species	Test Results	
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)			
Crustacea	EC50	Daphnia	100 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/L, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	8.8 mg/L, 96 hours
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential			
Mobility in soil			
Mobility in general	No data available.		
Other adverse effects	Not available.		
	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation)		

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
General	Canada: Marine Pollutants Exemption. 1.45.1. : Part 3, Documentation, and Part 4, Dangerous Goods Safety Marks, do not apply to substances that are classified as marine pollutants in accordance with section 2.43 of Part 2, Classification, if they are in transport solely on land by road vehicle or railway vehicle. However, substances may be identified as marine pollutants on a shipping document and the required dangerous goods safety marks may be displayed when they are in transport by road or railway vehicle. (SOR/2008-34, s. 23)
	US: DOT - 49 CFR 173.150 (f) - Combustible Liquid Exemption CFR 171.4: The requirements of this subchapter specific to marine pollutants does not apply to non-bulk packagings transported by motor vehicle, rail car or aircraft, except when all or part of the transportation is by vessel.
U.S. Department of Transportation (DOT)	Not regulated as dangerous goods.
Transportation of Dangerous Goods (TDG - Canada)	Not regulated as dangerous goods.

15. Regulatory Information

Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.	
Canada CEPA Schedule I: Listed substance		
2-Butanone, oxime (CAS 96-29-7)		Listed.
Ferric oxide (CAS 1309-37-1)		Listed.
Hydrous magnesium silicate (CAS 14807-96-6)		Listed.
Canada DSL Challenge Substances: Listed substance		
2-Butanone, oxime (CAS 96-29-7)		Listed.
Carbon black (CAS 1333-86-4)		Listed.
Crystalline silica (CAS 14808-60-7)		Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5) 1 TONNES
 Naphtha (petroleum), heavy alkylate (CAS 64741-65-7) 1 TONNES
 Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7) 1 TONNES
 Stoddard solvent (CAS 8052-41-3) 1 TONNES
 Xylene (CAS 1330-20-7) 1 TONNES

Canada Priority Substances List (Second List): Listed substance

Ferric oxide (CAS 1309-37-1) Listed.
 Hydrous magnesium silicate (CAS 14807-96-6) Listed.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Benzene, ethyl- (CAS 100-41-4) Listed.
 Manganese Oxide (CAS 1317-34-6) Listed.
 Xylene (CAS 1330-20-7) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Crystalline silica (CAS 14808-60-7) Cancer
 lung effects
 immune system effects
 kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Benzene, ethyl-	100-41-4	1-5*
Xylene	1330-20-7	10-30*

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Benzene, ethyl- (CAS 100-41-4)
 Manganese Oxide (CAS 1317-34-6)
 Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations**US - California Hazardous Substances (Director's): Listed substance**

Benzene, ethyl- (CAS 100-41-4) Listed.
 Carbon black (CAS 1333-86-4) Listed.
 Ferric oxide (CAS 1309-37-1) Listed.
 Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5) Listed.
 Hydrous magnesium silicate (CAS 14807-96-6) Listed.
 Manganese Oxide (CAS 1317-34-6) Listed.
 Naphtha (petroleum), heavy alkylate (CAS 64741-65-7) Listed.
 Silica, amorphous, fumed, crystalline free (CAS 112945-52-5) Listed.

Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.
US - Illinois Chemical Safety Act: Listed substance	
Benzene, ethyl- (CAS 100-41-4)	
Manganese Oxide (CAS 1317-34-6)	
Xylene (CAS 1330-20-7)	
US - Louisiana Spill Reporting: Listed substance	
Benzene, ethyl- (CAS 100-41-4)	Listed.
Manganese Oxide (CAS 1317-34-6)	Listed.
Xylene (CAS 1330-20-7)	Listed.
US - Michigan Critical Materials Register: Parameter number	
Xylene (CAS 1330-20-7)	XYLENE (ALL ISOMERS)
US - Minnesota Haz Subs: Listed substance	
2-Butanone, oxime (CAS 96-29-7)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Carbon black (CAS 1333-86-4)	Listed.
Crystalline silica (CAS 14808-60-7)	Listed.
Ferric oxide (CAS 1309-37-1)	Listed.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	Listed.
Hydrous magnesium silicate (CAS 14807-96-6)	Listed.
Manganese Oxide (CAS 1317-34-6)	Listed.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	Listed.
Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)	Listed.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.
US - New Jersey RTK - Substances: Listed substance	
Benzene, ethyl- (CAS 100-41-4)	
Carbon black (CAS 1333-86-4)	
Crystalline silica (CAS 14808-60-7)	
Ferric oxide (CAS 1309-37-1)	
Hydrous magnesium silicate (CAS 14807-96-6)	
Manganese Oxide (CAS 1317-34-6)	
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	
Stoddard solvent (CAS 8052-41-3)	
Xylene (CAS 1330-20-7)	
US - North Carolina Toxic Air Pollutants: Listed substance	
Manganese Oxide (CAS 1317-34-6)	
Xylene (CAS 1330-20-7)	
US - Texas Effects Screening Levels: Listed substance	
2-Butanone, oxime (CAS 96-29-7)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Carbon black (CAS 1333-86-4)	Listed.
Crystalline silica (CAS 14808-60-7)	Listed.
Ferric oxide (CAS 1309-37-1)	Listed.
Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)	Listed.
Hydrous magnesium silicate (CAS 14807-96-6)	Listed.
Manganese Oxide (CAS 1317-34-6)	Listed.
Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)	Listed.
Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)	Listed.
Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)	Listed.
Stoddard solvent (CAS 8052-41-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.
US - Washington Chemical of High Concern to Children: Listed substance	
Benzene, ethyl- (CAS 100-41-4)	
US. Massachusetts RTK - Substance List	
Benzene, ethyl- (CAS 100-41-4)	
Carbon black (CAS 1333-86-4)	
Crystalline silica (CAS 14808-60-7)	
Ferric oxide (CAS 1309-37-1)	
Hydrous magnesium silicate (CAS 14807-96-6)	

Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)
 Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)
 Stoddard solvent (CAS 8052-41-3)
 Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Benzene, ethyl- (CAS 100-41-4)
 Heavy aromatic solvent naphtha (petroleum) (CAS 64742-94-5)
 Manganese Oxide (CAS 1317-34-6)
 Solvent naphtha (petroleum), medium aliphatic (CAS 64742-88-7)
 Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Benzene, ethyl- (CAS 100-41-4)
 Carbon black (CAS 1333-86-4)
 Crystalline silica (CAS 14808-60-7)
 Ferric oxide (CAS 1309-37-1)
 Hydrous magnesium silicate (CAS 14807-96-6)
 Manganese Oxide (CAS 1317-34-6)
 Silica, amorphous, fumed, crystalline free (CAS 112945-52-5)
 Stoddard solvent (CAS 8052-41-3)
 Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Benzene, ethyl- (CAS 100-41-4)
 Carbon black (CAS 1333-86-4)
 Crystalline silica (CAS 14808-60-7)
 Ferric oxide (CAS 1309-37-1)
 Hydrous magnesium silicate (CAS 14807-96-6)
 Naphtha (petroleum), heavy alkylate (CAS 64741-65-7)
 Stoddard solvent (CAS 8052-41-3)
 Xylene (CAS 1330-20-7)

US. California Proposition 65



WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene, ethyl- (CAS 100-41-4)	Listed: June 11, 2004
Carbon black (CAS 1333-86-4)	Listed: February 21, 2003
Crystalline silica (CAS 14808-60-7)	Listed: October 1, 1988

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	* 2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 27-June-2018
Version # 03
Effective date 27-June-2018
Prepared by Dell Tech Laboratories, Ltd. Phone: (519) 858-5021

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.