



# Bona Craft Oil 2K<sup>®</sup> Care

Maintenance Oil for Previously Oiled Floors

Designed to refresh the oils and restore its protective qualities



Bona Craft Oil 2K<sup>®</sup> Care is used for the professional maintenance of oiled floors. It is a mixture of vegetable oils that delivers superior protection, allows for great coverage, and penetrates for fast saturation. Indoor air quality is maintained due to extremely low VOCs and its quick drying attribute.

- Restores look of oiled floor
- Very low VOC's
- Easy to apply
- Specifically designed for oiled floors



# Bona Craft Oil 2K<sup>®</sup> Care

Maintenance Oil for Previously Oiled Floors

Designed to refresh the oils and restore its protective qualities

## PHYSICAL CHARACTERISTICS

**Ingredients** – Vegetable oil, oil-modified polyurethane resin, petroleum distillates, wax, and driers

**VOC's** – 35 g/L (.30 pounds per gallon VOC)

## APPLICATION CHARACTERISTICS

**Dry time** – 12 hours (60-80 F and 35-75% relative humidity).

**Applicators** – Bona<sup>®</sup> Cut-In pad, Bona<sup>®</sup> steel trowel and Bona<sup>®</sup> Cotton Cloths or rubber bladed applicator.

**Coverage rate** – 600-1,200 sq. ft. per container

**Shelf life** – 2 years in unopened container

**Disposal** – Wastes and emptied containers should be handled in accordance with local regulations.

**Packaging** – 1 Liter plastic container

## RECOMMENDED USE

Commercial and residential use including shopping malls, restaurants, offices, retail stores, hospitals, schools, and nursing homes.

**BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS.**

**FOR TECHNICAL ADVICE:** Call Bona US at 800-872-5515

## RESPONSE

In case of eye contact, flush immediately with water. Get medical attention if irritation occurs. For skin, wash thoroughly with soap and water. If affected by inhalation, remove to fresh air. If swallowed, drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Get medical attention if symptoms occur.

## COMPATIBILITY

Bona Craft Oil 2K Care can be used on Bona Craft Oil 2K<sup>®</sup> or any natural penetrating oil. Product results may vary widely. ALWAYS PREPARE A SAMPLE OR

TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.

## THE BONA CRAFT OIL 2K CARE SYSTEM

Bona Craft Oil 2K Care is a maintenance oil for previously oiled floors, designed to refresh the oils and restore its protective qualities. Bona Craft Oil 2k Care should be applied as needed based on floors appearance. Visit [bona.com](http://bona.com) for additional product information.

**TIP:** If the surface is heavily worn and lost some of its pigmentation, it is possible to add up to 20% of the Bona Craft Oil 2K (Part A) in the corresponding color to Bona Craft Oil 2K Care Oil.

## RECOMMENDED APPLICATORS

Red buffing pad, Bona Cut-in Pad, Bona Steel Trowel and Bona Cotton Cloths.

## MIXING INSTRUCTIONS

SHAKE WELL BEFORE USING. DO NOT THIN. DO NOT ADD WATER.

## APPLICATION

1. Thoroughly clean floor using the Bona Deep Clean System or Bona Craft Oil 2K Soap following label directions. 2. Allow floor to dry completely. 3. Apply a thin coat of the Bona Craft Oil 2K Care to the floor using a 175 rpm buffer and a red buffing pad working back and forth with the grain of the wood when possible. For areas the buffer cannot reach, use a trowel or cut-in pad to apply. 4. Allow the oil to penetrate the wood surface for 15-30 minutes. 5. Remove excess oil using a buffer and a clean, Bona Cotton Cloth wrapped around a 1" white, red or green buffing pad. Change cotton cloth as needed. 6. Allow oil to dry thoroughly before use (12 hours under ideal conditions of 65-80 F and 40-60% relative humidity). High humidity and or low temperature conditions will extend dry time, while increased ventilation and airflow will reduce dry time. **BE SURE YOU ARE USING THE RECOMMENDED COVERAGE OF APPROXIMATELY 600-1,200 SQ.**



# Bona Craft Oil 2K<sup>®</sup> Care

Maintenance Oil for Previously Oiled Floors

**Designed to refresh the oils and restore its protective qualities**

FT. PER CONTAINER (coverage may vary dependent on condition of floor).

## CLEAN-UP

Application tools should be cleaned with mineral spirits

## STABILITY

Two year shelf life in unopened container.

## STORAGE

Bona Craft Oil 2k<sup>®</sup> should be stored in a climate-controlled environment. KEEP FROM FREEZING. Do not store above 100° F.

## DANGER

RAGS, STEEL WOOL OR WASTE SOAKED WITH BONA CRAFT OIL REFRESHER MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED, METAL CONTAINER.

## ORDERING INFORMATION

Item #	Size	No./Case	Weight (lbs.)
GT525113020	1 Liter	6	14.6 lbs.