



Distributed by:  
**ATOM Ventures, LLC**  
Chicago, IL 60613

866.563.6283  
www.GoodFilla.com

## TECHNICAL DATA SHEET

**Gork's GoodFilla**  
**Water-Based Wood/Grain Filler**

### PRODUCT DESCRIPTION

**GoodFilla® WATER-BASED WOOD FILLER** is a unique water-based multi-purpose wood and grain filler. **GoodFilla®** can be used to mask small or large defects. It can also be used as a grain filler, knot/MDF sealer, or primer. **GoodFilla®** can be used **inside** or outside and takes stains and paint evenly, making it ideal for any customer project. **GoodFilla®** spreads evenly into cracks and holes with no crumbling, cracking, or shrinkage. **GoodFilla®** is easily sanded to achieve a desired finished look.

### PRODUCT CHARACTERISTICS and BENEFITS

<b>High solid content</b>	Saw, drill, sand, plane, and nail—just like real wood
<b>Fast dry time</b>	Can be used indoors and outdoors (must be sealed for exterior use)
<b>Easy application</b>	Spreads evenly into cracks and holes without crumbling or cracking
<b>Superior strength</b>	Very hard finish with no perceptible shrinkage
<b>Quality finish</b>	Takes stains and any coating flawlessly
<b>Accepts any pigment</b>	Can be custom tinted with any stain, dye, or pigment.
<b>Multiple use</b>	Wood/MDF filler, grain filler, sealer, and primer

### PHYSICAL PROPERTIES

<b>Color(s)</b>	Maple/Ash/Pine, Cherry/Alder, Mahogany/Brazilian Cherry, Red Oak, Natural/Tint Base, White Oak, Rosewood, Walnut, White, Ebony (10 colors)
<b>Density</b>	14.8 – 15.8 lbs/gal
<b>Solids</b>	74% ± 1.5% (by weight)
<b>Storage</b>	Store between 45-85 °F (7-29 °C)
<b>Freeze/thaw stability</b>	Stable; Allow product to warm to room temperature before using
<b>Shelf life</b>	18 to 24 months (can be reconstituted with hot water.) Stir if product separation occurs.

### DIRECTIONS FOR USE/APPLICATION NOTES (voids and gaps)

Please read all directions before using. Always test a small area before full use.

- Step 1** Match **GoodFilla** color to wood. If staining use tint base/natural. Stain must always be darker than filler.
- Step 2** For best adhesion, cracks or defects should be clean and dry.
- Step 3** Press firmly into defect by hand, or with putty knife.
- Step 4** A thin film will dry within minutes. Lower temperatures require longer drying periods.
- Step 5** When dry, sand flush with surrounding surfaces.
- Step 6** Surfaces may be stained, clear-coated, painted, varnished, lacquered, waxed, or shellacked.
- Step 7** Clean tools while still wet with water or soap with water. If product has dried on tools, use hot water.
- Step 8** Close container after each use.

### DIRECTIONS FOR USE/APPLICATION NOTES (Grain filling/MDF primer/sealer)

Please read all directions before using. Always test a small area before full use.

- Step 1** Match **GoodFilla** color to wood. If staining use tint base/natural. Stain must always be darker than filler.
- Step 2** Mix **GoodFilla** with equal parts of warm water to filler.
- Step 3** Stir thoroughly.
- Step 4** Apply by hand with cloth. Use 1.6 mm–2mm nozzle for spraying application.
- Step 5** When dry, sand or use a damp cloth to flush with surrounding surfaces.
- Step 6** Surfaces may be stained, urethaned, painted, varnished, lacquered, waxed, or shellacked.
- Step 7** Clean tools while still wet with water or soap with water. If product has dried on tools, use hot water.

**Step 8** Close container after each use.

- \*Gork's GoodFilla® Water-Based Wood Filler can be drilled, nailed, planed, or sawed like ordinary wood.**
- \*Use water to restore wood filler to its original consistency.**

For technical assistance: 866.563.6283.

## **HAZARDS**

---

Before working with this product, read and become familiar with information concerning hazards, proper use and handling. To request an MSDS download one from [www.GoodFilla.com](http://www.GoodFilla.com), or please send an Email to [info@goodfilla.com](mailto:info@goodfilla.com) or call 866.563.6283.

## **LIMITED WARRANTY**

---

The product is warranted against any defect in materials or workmanship under normal use and service for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable state law, including, without limitation, the implied warranty of merchantability and the implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. This warranty covers only the original buyer of the product. This warranty does not include labor or the cost of labor for the application of this product. For warranty service, the buyer should contact the store where the product was purchased, or write ATOM Ventures LLC, P.O. Box 13206, Chicago, IL 60613. This warranty gives you specific legal rights, and you also have other rights, which vary from state to state.

