

Printing date 11/15/2017 Reviewed on 08/28/2017

1 Identification

1.1 Product identifier

Trade name: Osmo Liquid Wax Cleaner

Article number: 3029 clear, 3087 white

Application of the substance / the

mixture Maintenance product

Cleaning agent/ Cleaner

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Supplier:

Osmo Wood and Colour Canada Ltd.

5515 - 92 ST NW

Edmonton, Alberta T6E 3A4

Canada

Tel: 001 (877) 746 6583 E-mail: info@osmo.ca

Manufacturer

Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Germany

Information department: Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: 24h-Emergency Phone Number:

For Chemical Emergency, Spill; Leak; Fire Exposure or Accident Call Day or Night

within USA and Canada 1-800-424-9300

Outside USA and Canada 001-703-527-3887 (WISAG FMO cargo Services Gmbh &

Co.KG)

Importer Osmo Wood and Colour Canada Ltd.

5515 – 92 ST NW

Edmonton, Alberta T6E 3A4

Canada

Tel: 001 (877) 746 6583 E-mail: info@osmo.ca

2 Hazard identification

2.1 Classification of the substance or mixture

Classification according to Hazardous Products Regulations

Flam. Liq. 4 H227 Combustible liquid.

(Contd. on page 2)



Printing date 11/15/2017 Reviewed on 08/28/2017

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 1)

2.2 Label elements

Labelling according to Hazardous

Products Regulations The product is classified and labeled according to the CLP regulation.

Hazard pictograms Void
Signal word Warning

Hazard statementsH227 Combustible liquid.Precautionary statementsKeep out of reach of children.

If medical advice is needed, have product container or label at hand.

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Observe the general safety regulations when handling chemicals.

Additional information:

Hazard description:

WHMIS-symbols: B3 - Combustible liquid



Classification system:

NFPA ratings (scale 0 - 4) Health = 0

Fire = 2

Reactivity = 0

HMIS-ratings (scale 0 - 4) Health = 0

Fire = 2Reactivity = 0

2.3 Other hazards Not applicable.

3 Composition/Information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

64742-48-9 aliphatic hydrocarbons, C10-C13

(•• Asp. Tox. 1, H304; Flam. Liq. 4, H227

60-100%

4 First aid measures

4.1 Description of first aid measures

General information: Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Printing date 11/15/2017 Reviewed on 08/28/2017

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 2)

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Do not induce vomiting; immediately call for medical help.

If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and

effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available.

5 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or

alcohol resistant foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

Cool endangered receptacles with water spray.

6 Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections See Section 13 for disposal information.

(Contd. on page 4)



Printing date 11/15/2017 Reviewed on 08/28/2017

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 3)

7 Handling and storage

7.1 Precautions for safe handling Keep receptacles tightly sealed.

Use only in well ventilated areas.

Keep away from heat and direct sunlight.

Prevent formation of aerosols.

Information about protection

against explosions and fires: Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Store in a cool location.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

Further information about

storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 10

7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

Additional information about

design of technical systems: No further data; see item 7.

8.1 Control parameters

Components with limit values that

require monitoring at the

workplace: The product does not contain any relevant quantities of materials with critical values

that have to be monitored at the workplace.

Additional information: The lists that were valid during the creation were used as basis.

8.2 Exposure controls

Personal protective equipment: General protective and hygienic

measures: Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing.

Keep away from foodstuffs, beverages and feed.

Breathing equipment: Not necessary if room is well-ventilated.

(Contd. on page 5)



Printing date 11/15/2017 Reviewed on 08/28/2017

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 4)

Protection of hands: To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves Nitrile rubber, NBR

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.4 \text{ mm}$

For the mixture of chemicals mentioned below the penetration time has to be at least

480 minutes (Permeation according to EN 374 Part 3: Level 6).

As protection from splashes gloves made of the following

Upper:

Vapor pressure at 20 °C:

Density at 20 °C:

materials are suitable: Nitrile rubber, NBR

Eye protection: Goggles recommended during refilling.

7,0 Vol %

0,77-0,80 g/cm3 (DIN 51757)

<1 hPa

Body protection: Protective work clothing

9 Physical and chemical properties

9.1 Information on basic physical	al and chemical properties
General Information	
Appearance:	
Form:	Fluid
Color:	According to product specification
Odor:	Mild
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	180-210 °C
Flash point:	~62 °C (DIN 53213)
Ignition temperature:	~200 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures an
	possible.
Explosion limits:	
Lower:	0,6 Vol %

(Contd. on page 6)



Printing date 11/15/2017 Reviewed on 08/28/2017

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 5)

Relative densityNot determined.Evaporation rateNot determined.

Solubility in / Miscibility with

Water: Insoluble.

Viscosity:

Dynamic at 23 °C: ~18 mPas (DIN 53214)

Kinematic at 40 °C: $> 20 \text{ mm}^2/\text{s}$

9.2 Other information No further relevant information available.

10 Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition

products: No hazardous decomposition products when stored and handled correctly.

11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50	values i	that	are re	levant fo	or cl	lassificati	on:
---------	----------	------	--------	-----------	-------	-------------	-----

64742-48-9 aliphatic hydrocarbons, C10-C13

Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
Dermal	LD50	> 5000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

Primary irritant effect:

on the skin: At long or repeated contact with skin it may cause dermatitis due to the degreasing

effect of the solvent.

on the eye: Based on available data, the classification criteria are not met.Sensitization: Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 11/15/2017 Reviewed on 08/28/2017

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 6)

Additional toxicological information:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

12.1 Toxicity

Aquatic toxicity:		
64742-48-9 aliphatic hydrocarbons, C10-C13		
EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)	
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)	
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)	
Biolog. Abbaubarkeit	(leicht abbaubar)	

12.2 Persistence and degradability No further relevant information available.
 12.3 Bioaccumulative potential No further relevant information available.
 12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (Self-assesment): slightly hazardous for water

12.5 Results of PBT and vPvB assessment

PBT:Not applicable.vPvB:Not applicable.

12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

13.1 Waste treatment methods

Recommendation: Must not be disposed of together with household garbage. Do not allow product to

reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Solvent naphtha

(Contd. on page 8)



Printing date 11/15/2017 Reviewed on 08/28/2017

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 7)

14 Transport information	
14.1 UN-Number DOT, TDG, ADN, IMDG, IATA	Void
14.2 UN proper shipping name	
DOT, TDG, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
DOT, TDG, ADN, IMDG, IATA	
Class	Void
14.4 Packing group	
DOT, TDG, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Transport in bulk according to Anne	ex II of
MARPOL73/78 and the IBC Code	Not applicable.
UN ''Model Regulation'':	Void

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Sara

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed.

Canadian substance listings:

Canadian Domestic Substances List (DSL)

All ingredients are listed.

Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

(Contd. on page 9)



Printing date 11/15/2017 Reviewed on 08/28/2017

Trade name: Osmo Liquid Wax Cleaner

(Contd. of page 8)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Date of preparation / last revision 11/15/2017 / 11

Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

CA