

SAFETY DATA SHEET

1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation:

Name: LAKEONE french polish restorer

Product code: 20303

Company/undertaking identification:

Registered company name: INITIATIVES DECORATION.

Address: ZI DES SOEURS 20 AVENUE ANDRE DULIN BP30027.17301.ROCHEFORT CEDEX.france.

Telephone: 05-46-88-88-00. Fax: 05-46-88-88-01.

c.micollier@groupe-id.com

http://www.les-anciens-ebenistes.com
Emergency telephone: 01-45-42-59-59.
Association/Organisation: ORPHILA.
Use of the substance/preparation:
Polish up French polished furniture

2 - HAZARDS IDENTIFICATION

This product is classified: Highly flammable liquid. Vapors may cause drowsiness and dizziness.

Preparation classification:



R 11	Highly flammable.
R 67	Vapours may cause drowsiness and dizziness.

3 - COMPOSITION/INFORMATION ON INGREDIENTS

Full text of risk phrases appearing in section 3: see section 16.

Hazardous substances present on their own:

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state) This preparation contains no hazardous substance in this category.

Other substances representing a hazard:

INDEX	CAS	EC	Name	Symb.	R:	%
603-127-00-5	78-92-2	201-158-5	BUTAN-2-OL	Xi	10 36/37 67	10 <= x % < 25
Substances n	recent at a canaa	ntration balaus th	o minimum dangar throobalds			-

Substances present at a concentration below the minimum danger threshold:

INDEX	CAS	EC	Name	Symb.	R:	%	
603-001-00-X	67-56-1	200-659-6	METHANOL	ΤF	11 23/24/25	0 <= x % < 2.5	
					39/23/24/25		

Other substances with occupational exposure limits:

INDEX	CAS	EC	Name	Symb.	R:	%
603-002-00-5	64-17-5	200-578-6	ETHANOL	F	11	25 <= x % < 50

4 - FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing in an unconscious person.

In the event of exposure by inhalation:

20303 - LAKEONE french polish restorer

If a large quantity is inhaled, move the patient into the fresh air and keep him/her warm and still.

In the event of splashes or contact with eyes:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

DO NOT use solvents or thinners.

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

Page: 2/5

Version: 12.1 (24-02-2011)

5 - FIRE-FIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

Suitable extinguishing media:

Special foams for polar liquids (known as alcohol resistant), powders, carbon dioxide.

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Extinguishing media which must not be used for safety reasons:

Water is not generally recommended since it can be ineffective; however, it can be used successfully to cool containers exposed to the fire and to disperse fumes.

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Special protective equipment for fire-fighters:

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions:

On account of the organic solvents contained in the preparation, eliminate sources of ignition and ventilate the premises.

Avoid inhaling the vapors.

Consult the safety measures listed under headings 7 and 8.

Environmental precautions:

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Methods for cleaning up:

Clean preferably with a detergent, do not use solvents.

To be translated (XML)

7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

Handling:

Handle in well-ventilated areas.

Fire prevention:

Use the product in premises where there are no naked flames or other sources of ignition and have protected electrical equipment Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Recommended equipment and procedures:

For personal safety, see §8.

Observe precautions stated on label and also industrial safety regulations

Packages which have been opened must be reclosed carefully and stored in an upright position

Avoid inhaling vapors.

Prohibited equipment and procedures:

Smoking, eating and drinking are prohibited in premises where the preparation is used

20303 - LAKEONE french polish restorer

Never open the packages under pressure

Storage:

Keep the container tightly closed in a dry, well-ventilated place

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Use personal protection equipment as per Directive 89/686/EEC.

Technical measures:

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.

If this ventilation is insufficient to maintain the concentration of solvent vapors below the exposure limits, wear breathing apparatus

Exposure limit values per INRS ED 984:

France	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP N°:
78-92-2	100	300	-	-	-	84
64-17-5	1000	1900	5000	9500	-	84
67-56-1	200	260	-	-	(12)	84

Page: 3/5

Version: 12.1 (24-02-2011)

Exposure limit values per 2006/15/CE, 2000/39/EC and 98/24/EC:

EC	VME-mg/m3:	VME-ppm:	VLE-mg/m3:	VLE-ppm:	Notes:
67-56-1	260	200	-	-	Peau

Exposure limit values (2003-2006):

UK/WELs	TWA:	STEL:	Ceiling:	Definition:	Criterion:
78-92-2	100 ppm	150 ppm	-	-	-
64-17-5	1000 ppm	-	-	-	-
67-56-1	200 ppm	250 ppm	-	-	-
UK/OES	TWA:	STEL:	Ceiling:	Definition:	Criterion:
78-92-2	100 ppm	150 ppm	-	-	-
64-17-5	1000 ppm	-	-	-	-
67-56-1	200 ppm	250 ppm	-	-	-

Respiratory protection:

Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks.

Hand protection:

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.

In the event of prolonged or repeated contact with the hands, use appropriate gloves.

To be translated (XML)

Eye and face protection:

Use eye protectors designed to protect against liquid splashes

Skin protection:

For further information, see § 11 of S.D.S. - Toxicological information.

9 - PHYSICAL AND CHEMICAL PROPERTIES

General information:

Self-ignition temperature:

VOC (g/l):

Physical state:

,	Linear inflation
Important health, safety and environmental infor	mation:
pH of the substance or preparation:	not relevant.
The pH is impossible to measure or its value is no	ot relevant.
Boiling point/boiling range:	not specified.
Flash point interval:	Flash point <= 21°C
Vapour pressure:	Between 110 kPa and 175 kPa inclusive.
Density:	<1
Water solubility:	Insoluble.
Other information:	
melting point/melting range:	not specified.

fluid liquid

not specified.

not specified.

5.68

10 - STABILITY AND REACTIVITY

Decomposition point/decomposition range:

When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide,

20303 - LAKEONE french polish restorer

Version: 12.1 (24-02-2011)

smoke and nitrogen oxide

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Page: 4/5

Conditions to avoid:

protect from heat

Materials to avoid:

nitrocellulose decomposes on contact with alkalis, corrosive substances and potent oxidizing agents

11 - TOXICOLOGICAL INFORMATION

No data is available regarding the preparation itself.

Splashes in the eyes may cause irritation and reversible damage

In the event of swallowing:

To be translated (XML)

In the event of splashes or contact with skin:

To be translated (XML)

In the event of splashes or contact with eyes:

To be translated (XML)

Other data:

CAS 64-17-5: IARC Group 1: The agent is carcinogenic to humans.

12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

The product must not be allowed to run into drains or waterways.

13 - DISPOSAL CONSIDERATIONS

Do not pour into drains or waterways.

Waste:

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

14 - TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2009 -IMDG 2008 - ICAO/IATA 2011).

Classification:

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

	, -		5		- /					
ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	II	3	33	LQ6	163 640C 650	E2	2	D/E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	3	-	II.	5 L	F-E,S-E	163	E2			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	3	-	II	353	5 L	364	60 L	A3 A72	E2	
	3	-	ll .	Y341	1 L	-	-	A3 A72	E2	

15 - REGULATORY INFORMATION

Classification by:

So called 'all preparations' Directive 1999/45/EC and its adaptations.

EC regulation 1272/2008 (CLP) and its adaptations (EC regulation 790/2009).

Preparation classification:

Page : 5/5

Version: 12.1 (24-02-2011)



Particular hazards associated with the preparation and safety recommendations:

R 11	Highly flammable.
R 67	Vapours may cause drowsiness and dizziness.
S 2	Keep out of the reach of children.
S 46	If swallowed, seek medical advice immediately and show this container or label.
S 16	Keep away from sources of ignition - No smoking.
S 51	Use only in well-ventilated areas.

Particular provisions:

Tactile warning of danger.

16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties

Full text of risk phrases appearing in section 3:

R 10	Flammable.
R 11	Highly flammable.
R 23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R 36/37	Irritating to eyes and respiratory system.
R 39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if
	swallowed.
R 67	Vapours may cause drowsiness and dizziness.