Page: 1/4

Version: 6.2 (25-07-2007)

SAFETY DATA SHEET

1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation:

Name: LAKEONE wood dve medium oak

Product code: 50101:03

Company/undertaking identification:

Registered company name: INITIATIVES DECORATION.

Address: ZI DES SOEURS 20 AVENUE ANDRE DULIN BP30027.17301.ROCHEFORT CEDEX.france.

Telephone: 05-46-88-88-00. Fax:05-46-88-88-01. Telex:.

c.micollier@groupe-id.com

http://www.les-anciens-ebenistes.com Emergency telephone: 01-45--42-59-59. Association/Organisation: ORPHILA. Use of the substance/preparation:

wood stain

2 - HAZARDS IDENTIFICATION

This product is classed: Flammable. May produce an allergic reaction.

Preparation classification:

Flammable.

R 10 Flammable.

3 - COMPOSITION/INFORMATION ON INGREDIENTS

Full text of risk phrases appearing in section 3: see section 16.

Hazardous substances present on their own:

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state) This preparation contains no hazardous substance in this category.

Other substances representing a hazard:

No known substance in this category present.

Substances present at a concentration below the minimum danger threshold:

INDEX	CAS	EC	Name	Symb.	R:	%
603-001-00-X	67-56-1	200-659-6	METHANOL	ΤF	11 23/24/25	0 <= x % < 2.5
					39/23/24/25	

Other substances with occupational exposure limits:

INDEX	CAS	EC	Name	Symb.	R:	%
603-002-00-5	64-17-5	200-578-6	ETHANOL	F	11	2.5 <= x % < 10

May produce an allergic reaction:

.,,,							
INDEX	CAS	EC	Name	Symb.	R:	%	
A021			ACIDE JAUNE42	Xi	41 43	0 <= x % < 2.5	

4 - FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing in an unconscious person.

50101:03 - LAKEONE wood dye medium oak Version : 6.2 (25-07-2007)

Page: 2/4

In the event of splashes or contact with eyes:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

DO NOT use solvents or thinners.

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

5 - FIRE-FIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

Suitable extinguishing media:

Special foams for polar liquids (known as alcohol resistant), powders, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Water is not generally recommended since it can be ineffective; however, it can be used successfully to cool containers exposed to the fire and to disperse fumes.

Sometimes, and due to the presence of organic material, a fire may produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Special protective equipment for fire-fighters:

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions:

Avoid inhaling the vapors.

Consult the safety measures listed under headings 7 and 8.

Environmental precautions:

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Methods for cleaning up:

Clean preferably with a detergent, do not use solvents.

7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

Fire prevention:

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Recommended equipment and procedures:

For personal safety, see §8.

Observe precautions stated on label and also industrial safety regulations

Avoid inhaling vapors.

Prohibited equipment and procedures:

Smoking, eating and drinking are prohibited in premises where the preparation is used

Never open the packages under pressure

Storage:

Keep the container tightly closed in a dry place.

To be translated (XML)

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Use personal protection equipment as per Directive 89/686/EEC.

Exposure limit values per INRS ED 984:

SAFETY DATA SHEET (EC N°1907/2006) 50101:03 - LAKEONE wood dye medium oak

Version: 6.2 (25-07-2007)

Page: 3/4

France	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP N°:
64-17-5	1000	1900	5000	9500	-	84
67-56-1	200	260	1000	1300	-	84

Exposure limit values per 2006/15/CE, 2000/39/EC and 98/24/EC:

EC	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:
67-56-1	260	200	-	-	Peau

Exposure limit values (2003-2006):

UK/WELs	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
64-17-5	1000 ppm	-	-	-	-	
67-56-1	200 ppm	250 ppm	-	-	-	
UK/OES	TWA:	STEL:	Ceiling:	Definition:	Criterion:	
64-17-5	1000 ppm	-	-	-	-	
67-56-1	200 ppm	250 ppm	-	-	-	

Hand protection:

Type of gloves recommended:

- Butyl rubber

Skin protection:

For further information, see § 11 of S.D.S. - Toxicological information.

9 - PHYSICAL AND CHEMICAL PROPERTIES

General information:

Physical state:

Important health, safety and environmental information:					
pH of the substance or preparation:	slightly basic.				
When a pH measure is possible, it has a value of:	not stated.				
Boiling point/boiling range:	not specified.				
Flash point interval:	23°C. < Flash point: <= 55°C.				
vapour pressure:	Below 110 kPa (1.10 bar).				
Density:	= 1				
water solubility:	Soluble.				

fluid liquid

Other information:

melting point/melting range:	not specified.
Self-ignition temperature:	not specified.
Decomposition point/decomposition range :	not specified.

10 - STABILITY AND REACTIVITY

The preparation is stable at the handling and storage conditions recommended per § 7 of the safety data sheet,

Conditions to avoid:

To be translated (XML)

Materials to avoid:

potent oxidizing agents potent acids

11 - TOXICOLOGICAL INFORMATION

No data is available regarding the preparation itself.

Splashes in the eyes may cause irritation and reversible damage

In the event of splashes or contact with skin:

To be translated (XML)

In the event of splashes or contact with eyes:

To be translated (XML)

12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

The product must not be allowed to run into drains or waterways.

13 - DISPOSAL CONSIDERATIONS

Page : 4/4

50101:03 - LAKEONE wood dye medium oak Version : 6.2 (25-07-2007)

Do not pour into drains or waterways.

Waste

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

14 - TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2007 - IMDG 2006 - ICAO/IATA 2007).

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	
	3	F1	III	3	30	LQ7	163 640 650E	
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.		
	3	-	III	5 L	F-E,S-E	163 223 944 955		
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note
	3	-	Ш	309	60 L	310	220 L	A3 A72
	3	-	Ш	Y309	10 L	-	-	-

15 - REGULATORY INFORMATION

This preparation was classified in compliance with the directive known as <All preparations> 1999/45/EC and its adaptations In addition directive 2004/73/EC with the 29° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.

Preparation classification:

Flammable.

Contains:

Contains A021	ACIDE JAUNE42. May produce an allergic reaction.		
Particular hazards associated with the preparation and safety recommendations:			
R 10	Flammable.		
S 2	Keep out of the reach of children.		
S 46	If swallowed, seek medical advice immediately and show this container or label.		

16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties

Full text of risk phrases appearing in section 3:

R 11	Highly flammable.
R 23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R 39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if
	swallowed.
R 41	Risk of serious damage to eyes.
R 43	May cause sensitisation by skin contact.