

TECHNICAL DATA SHEET

Pro.Oil

Transparent and coloured protective base coat oil



3 Lt

DESCRIPTION

Product based on vegetable oils formulated to protect wood floors. It penetrates deep down, bringing out the characteristic smoothness and warmth of wood, while highlighting the grain.

Available in the neutral version (Pro.Oil) and coloured version (Pro.Oil Color– see the Vermeister colour chart).

TECHNICAL DATA CHEMICAL-PHYSICAL CHARACTERISTICS at 65°F (indicative values not constituting product specifications):	
Application method	Roller, brush, pad, spatula, single disc buffer
Interval before polishing (min)	5/15
Ready for traffic and overcoating (hours)	12/24
Average coverage per coat (sq.ft./Lt)	200/300
Stability and storage (in original, unopened containers stored in a cool, dry place) (months)	12
To clean tools	DILUENTE PLUS
Standard packaging (Lt)	3

APPLICATION

To optimise the application of both coloured and neutral oils, it is essential to prepare the base with the utmost care, removing all traces of any previous finishing treatment and using a fine grit paper 100/120 last to sand the floor. Vacuum carefully to remove all traces of dust and/or impurities and proceed with the application of a thin, uniform coat of coloured or neutral Pro.Oil using a roller (black with short hair), brush, pad, trowel or wax spreader. After about 5/15 minutes, polish using a single disc buffer with a white or beige pad (excessively long intervals may make polishing difficult and in the case of high quantities of product an absorbent cloth must be placed under the disc to soak up the excess oil).

Pro.Oil and Pro.Oil Color may also be applied directly using a single disc buffer and a white or beige disc, adding small quantities of product to the centre of the pad and massaging until it is spread evenly.

After 12/24 hours, the finishing coat of Fix.Oil or Fix.Oil Light can be applied (see relevant technical data sheet).

NOTES

Floors treated with Pro.Oil and Pro.Oil Color must always be finished with highly resistant finishing oil Fix.Oil or Fix.Oil Light.

Shake well before use.

Safety precautions ANY RESIDUE PRODUCT COULD SELF-COMBUST and cloths and tools impregnated with the oil must be soaked in water and, before being disposed of, they must be left to dry in the open air, in areas where there are no risks of flames spreading. Keep the product in a tightly closed, upright container in a cool place away from sources of heat. The product is classified and coded in compliance with EC Directives/regulations concerning hazardous substances. The information for the user is given in the relevant safety sheet. Empty containers or those containing slight traces of the product must be disposed of in accordance with local regulations. VerMeister S.p.A. guarantees that the details given in this sheet are provided to the best of the company's technical-scientific knowledge and experience; however, the company cannot be held responsible in any way for the results obtained with the products as the conditions of application are beyond the company's control. It is always advisable to check the suitability of the product to each specific circumstance. This sheet cancels and replaces all previous editions.