



SUPER ECO REMOVER

Super ECO Remover is made to remove conventional paints, varnishes and surface wood stains. To remove very resistant or industrial finishes, it is recommended to use the original Super Remover.

LIMITED WARRANTY: THE SELLER AND THE MANUFACTURER WILL NOT ACCEPT LIABILITY FOR MORE THAN THE REPLACEMENT OF THIS PRODUCT.

Directions

Prior to stripping, it is important to know that each stripping project is unique, and the product's responsiveness and waiting period will vary based on the surface to be stripped and the stripping tools used.

Interior: Use only in a well-ventilated area.

Exterior: avoid using the Super Remover under direct sunlight. Use the product at a temperature between 10 °C and 25° C in a well-ventilated area. Do not use the product on a rainy day because the Super Remover is water soluble. Do not use on a day with strong wind because the Super Remover is a volatile solvent.

Pour the Super ECO Remover directly onto the surface to be stripped. Using a pure bristle paint brush, spread the product so that a layer at least 3 mm thick, i.e., the thickness of two 2\$ coins, covers the surface to be stripped. Apply a thicker coat if there are 4 coats or more to remove. Dab the angles, moldings and patterns so the product can act in all gaps and corners. Let stand at least 30 minutes. Do not rush this step but do not let the product dry. Let it work longer if there are many layers.

Once the surface is ready to be stripped, use a spatula or a scraper to remove residues. Using a stripping pad and a bit of Super ECO Remover, remove any coating still remaining. Use a pointed tool or sharpened wooden dowel for angles and patterns.

For wood: Always work along the wood's grain not to damage it. Once the stripping is done, if desired, use methyl hydrate to clean the surface thoroughly.

Tips and tricks

Sans frais/ Toll free
Tel: 1 866 772-2948
Fax: 1 866 427-1040
info@superremover.com

Distributions J. Des Serres

C.P. 12, Granby, QC J2G 8E2



Work section by section and one section at the time to not allow the product to dry.

Under normal storage conditions (around 20°C), the product's consistency is similar to shampoo. To increase its viscosity, for example to facilitate vertical surface stripping, store the closed Super ECO Remover container one hour in the refrigerator before applying the product. It will be thicker and thus slide slower along the surface.

Plan to use a rather narrow scraper (around 5 cm in width), because the wider the scraper, the less contact it makes with the surface. Indeed, you will have to work double time to remove the residues left behind by the initial scraping!

Do not use on fiberglass, vinyl, linoleum, rubber, acrylic and plastics.

Consult your municipality's regulations for safe disposal of the product.

Warning

1. Always take all necessary precautions in order to avoid contact with eyes and skin. Wear a mask, chemical-resistant neoprene coated gloves and safety glasses. Do not breathe vapors.
2. In case of contact with skin, rinse with water to neutralize the product.
3. If in eyes, rinse with water for at least 20 minutes.
4. If inhaled, move the person to fresh air.
5. If swallowed, get immediate medical assistance. Do not induce vomiting.
6. Work in a fresh place away from sunshine and in a well-ventilated area.
7. Keep away from any heat source, flames or sparks.
8. Keep out of reach of children.

Sans frais/ Toll free
Tel: 1 866 772-2948
Fax: 1 866 427-1040
info@superremover.com

Distributions J. Des Serres

C.P. 12, Granby, QC J2G 8E2