

### Brio Zero

#### Finish for Wooden Walls & Ceilings

Oil emulsion for walls, ceilings, structures and other wooden surfaces finishing. In one single application, Brio Zero colors, seals and waterproofs wood without masking its details.

#### Preparation

Stir well with a stick before and while using. Apply at temperatures above 10 °C. Wood must be sanded with 150 grit sandpaper and vacuumed to remove any dust. **Prior to application on maple wood**, wet the wood, let dry 2 hours and sand lightly with a 220 grit sandpaper.

#### Application

Apply with a stain pad or a paintbrush.

#### Number of Coats

1 coat

For interior windows, it is strongly recommended to apply 1 coat of Brio Zero colorless over the colored coat. .

For a more intense color, it is possible to apply a second coat after 6 hours. However, if more than 24 hours have passed since the first application, sand the surface with a 150 grit sandpaper before applying the second coat.

#### Drying Time

6 hours

#### Covering

100 to 200 sq ft / L

#### Tools Cleaning

Soapy water

#### Composition

Modified vegetable oils, water, UV filters, iron oxides.

#### Maintenance

- Yearly cleaning : Bonito soap
- To refresh and make the surface shine : Colorless Brio Zero



- Zero solvent
- VOCs under 8 g / L
- Colors and seals wood in a single application
- Waterproofs wooden surfaces
- Dries rapidly
- Does not raise the wood fiber
- Available in 10 colors
- Prevents wood discoloration
- Great covering power
- Leaves no film on the wood surface
- Allows the wood vein to show through
- Easy to apply
- Lets the wood breathe
- Low odor

#### Project Types

Paneling for walls and ceilings, moldings, structures, interior doors

#### Surface Types

Wood, Cork

#### Compatibility

Can be covered with: Brio Zero Colorless, Secondo, wood varnish, wood wax.

**Durability**

8 to 15 years

**Storage**

Must not freeze. Store in an airtight container at room temperature.

**Residues Disposal**

Consult your municipality to properly dispose the remains of this product.

**Origin**

Italy

**Warranty**

Tembi products guarantee the quality of its products. They comply with the description given in the data sheets and proper labels for their intended use, in accordance with the instructions indicated by the company. However, since the manufacturer has no control over the circumstances, methods and usage conditions, this warranty covers only the high quality of Prato-Verde products.

**VOCs**

< 8 g / L

**Sheen**

Satin matt (2 à 6%)

**Sizes**

- 20 ml (sample)
- 237 ml
- 946 ml
- 3.78 L
- 18.9 L

**Colors**

- 100 - Colorless
- 101 - Natural\*
- 102 - White
- 103 - Grey
- 104 - Cherry
- 105 - Medium Oak
- 106 - Old Pine
- 107 - Burn wood
- 108 - Chocowood
- 109 - Dark Oak

\*The *101 - Natural* color is used to preserve the whiteness of white woods (white pine, maple, cedar, spruce, beech, aspen). Do not use *Natural* color on open grain wood (oak, walnut, mahogany, elm) or on colored wood.